
Australian House and Garden Practical Planning Series No. 5





Plans For Your
DREAMS
HOME

Noted Architects' Plans for **25 HOMES**



All 12-Squares and Under





DREAM YOURSELF A HOUSE FROM THESE OUTSTANDING DESIGNS!

SURPRISE IDEAS IN EVERY PLAN; HOUSES FOR FLAT AND SLOPING BLOCKS; COST-CUTTING BASIC PLANS; SPACIOUS HOMES FOR BIG AND SMALL FAMILIES: MIRACLE PLANS FOR TINY LOTS; PLANS TO SUIT EVERYONE!



PLANNING YOUR **NEW HOME?**

choose your taps before you build!



TAPS ARE A VERY IMPORTANT ITEM IN ANY HOME

How many times during a day do YOU turn on a tap in your home? You have, probably, never stopped to notice.

Actually, the number makes little difference. What DOES count is the pleasure and efficiency gained from your taps. That is why it is essential to choose taps that blend in perfect harmony with the design of your kitchen, bathroom or laundry. Taps that operate at the touch of a finger to give you an even, perfectly controlled flow.

G. E. CRANE PTY. LTD. have a range of taps designed to suit your every need — and they have been manufacturing taps of the highest quality for just

on ninety years.

Take for instance the very famous "Planet" model. A fine example of modern "easy-clean" brassware, Planet taps have been brassware, designed with smoothly sweeping lines to facilitate cleaning and polishing. There are no cracks or corners to collect stubborn, unsightly grease and grime. Take a tip from some of the leading architects of today — specify TAPS — by CRANE.






PLANET BATHROOM BASIN TAPS

Shown at left are a hot and cold set of Crane's "Planet" series basin sets. Beautifully finished in sparkling chrome, these taps have elevated spouts (see photograph above) so that more actual "basin space" is available.

Also shown above are "Recess cocks" for shower walls. Sturdy, heavily chrome plated, these shower control taps operate so lightly that even the most slippery of fingers can easily turn them on and off,



Combining rugged construction with clean beauty of appearance, the taps sketched above (and shown top left of photograph) are ideal for kitchen and laundry use.

Also manufactured by G. E. Crane are the "Comet" taps (right side of photograph). Designed by craftsmen for those who want "something for those who want "something different", these taps are made for basins, baths, tubs, sinks and showers.



G. E. CRANE PTY. LTD.

G. E. CRANE PTY. LTD., Ross St. and St. John's Rd., Forest Lodge. MW 2584.

CRANE (VICTORIA) PTY. LTD., 400 Victoria St., Nth. Melbourne. FY 1311. Offices in all other States.

Please	post	this	coupon	for	leaflets	displaying
TAPS B						, , ,
NAME						

ADDRESS

Australian House and Garden

Plans For Your

KEN G. MURRAYPublisher BERYL GUERTNER _____Editor MERTON JONESArt Supervision MARY SIMPSON Production

CONTENTS

(C Have a Triumph in small scale

61 SQUARES:	6½-Square House a Triumph in small-scale comfort		5
7½ SQUARES:	Full-Scale Living in 7½ Squares		6
8 SQUARES:	"Post and Beam" Method makes building economical		8
81 SQUARES:	Variety in 8½ Squares		7
	W. Watson Sharp		
9 SQUARES:	A 3-Stage Plan John Parkes 9-Square Plan for Seaside or Suburb)	1
	Viwa Turner) 1	12
94 SQUARES:	For a Block With No View E. Buhrich) 1	13
9½ SQUARES:	A Gem of a House)	16
10 SQUARES:	Realistic Plan is Budget Beater		
2000	A Home With a Verandah Viwa Turner)	18
The state of the s	Outstanding Plan for Family Living		
	No Waste Space in 10-Square Home)	24
A Carried Mark	John P. Ley		26
101 SQUARES:	Appealing Plan Has Alternative Treatment		
	John P. Ley	0	21
11 SQUARES:	Easy-Going Dignity to this II-Square House		
	Split-Levels — A Bonus in Space	D	28
	Viwa Turner	D	33
114 SQUARES:	Brick Modern John P. Ley	D	40
111 SQUARES:	Traditional Look - Modern Workability	1	
	John P. Ley John P. Ley John P. Ley		30 42
10 COULDED			44
12 SQUARES:	A Small Colonial House W. Watson Sharp Distinctive 2-Storey House John P. Ley		47
	Simplified Plan Suits 40' to 60' Block		48
A STATE OF THE STA	W. Watson Sharp (A Plan to Satisfy Most Family Needs		70
	W. Watson Sharp		51
	A Little Beauty for a Narrow Lot		52
	This House Faces Front or Side John P. Ley		
SPECIAL FEATUR	RES:		
What Yo	u Should Know About:		15
	Foundations Roofing		15
	White-Ant Proofing		34
	Home Lighting		39
Printed by Kenr	nure Press Pty. Ltd., Wetherill Street, North Lide	om	be,

N.S.W., for HOUSE and GARDEN Magazine Pty. Ltd., 142 Clarence Street, Sydney, BX 3761. Produced by the K. G. Murray Publishing Company Pty. Ltd., Sydney.

DISTRIBUTORS: GORDON & GOTCH (A/SIA) LTD., MELBOURNE

HOUSE AND GARDEN MAGAZINE PTY. LTD., SYDNEY.

No. 5 of the Australian House & Garden 'PRACTICAL PLANNING SERIES'

EDITORIAL

This is a book of ideas — ideas that will help you plan and build your own home. Thousands of couples will either build a home this year or plan one for the future. This book is published to give every one of them good advice, imaginative ideas, and

of them good advice, imaginative ideas, and at least one plan under 12 squares that is really their dream house.


When you plan a house, you need the help of a reputable architect. You need his careful consideration for detail and design, his experience in building. This book supplies your need, for all these home plans are drawn up by well-known architects. plans are drawn up by well-known architects who have found that designing minimum houses can be a challenging and absorbing

who have tound that designing minimum houses can be a challenging and absorbing project.
You can take any one of these designs along to builder or architect to show him the house you want. Or write to the architect of the plan you like or to the Editor—we are here to help you.

Our architects have designed small but not cramped family homes. They have given close attention to putting space where it is most useful. The results show spacious living rooms, kitchens that are efficient workrooms and bathrooms which are large enough to avoid family traffic jams. Newly-marrieds, young families, families where the children have grown up, all have an interest in this book of ideas.

If you want to work out the approximate cost of a particular house, here's how to do it. The average price per square (100 square feet) for a timber house is £320; for brick, £380; for asbestos cement, £300. Determine how many squares the plan is (it's plainly stated for each plan) and multiply it by these average costs. For example, a 10-square timber house would cost around £3,200. Quotations vary from builder to builder, from district to district, but this system will give you a rough guide.

There's more to a house than choosing the plan. If you know some of the tundamentals of home building, you can save yourself time, worry and money. So included in this plan book are features on foundation work, white ant proofing, lighting and roofing. Whatever your taste in houses, whether you have the money to build or are saving at this moment, if you are a prospective home owner, here is a book you should read.



Build your home in Timber



Large or small, a Timber home is best

TIMBER GIVES YOU -

- * More value for less money.
- ★ Comfort cooler in summer, warmer in winter.
- * Full play for the magic of colour.
- ★ Individuality expression for your own design ideas.
- ★ Full scope for the charm of modern design.
- ★ Unmatched beauty and style both inside and out.
- ★ Flexibility speedy and economical enlargement or remodelling.

BEAUTIFUL HOMES ARE ALWAYS BUILT IN TIMBER.



FILL IN COUPON AND MAIL TO -

Please send me a copy of the Timber Home Booklet (containing timber home plan ideas). Enclosed is my remittance for 2/- plus postage.

NAME

ADDRESS

"H.G.A."

Timber Development


ASSOCIATION of AUSTRALIA

(N.S.W. BRANCH) LTD.

19-23 Bligh Street, Sydney - Tel.: BW 7735 BW 9794

Contact us for practical home-planning advice, or any other aspects of timber use.

T.D.A. Services are Free - Without Fee or Obligation.



Looking from the patio to the house. The timber louvres above the awning-type windows are controlled from the inside by sliding panels at the back of the louvres. Cement blocks pave terrace.

$6\frac{1}{2}$ -Square House...

A triumph in small-scale comfort

Architect, John P. Ley, B.Arch A.R.A.I.A. A.R.I.B.A. PLAN No. 1

Descriptive Outline

Vertical and horizontal boarding. Corr. asb, cement or malthoid on battens. 64 squares.

Colour Suggestion

EAVES

Natural timber for horizontal boarding WALLS · lime yellow for vertical boarding. ROOF Natural. TRIM Deep gold. Deep golden yellow. Slate blue. DOOR

asbestos cement or malthoid on battens. As shown in the sketches, there are fixed, horizontal timber louvres above the windows, which are controlled

T'S surprising how comfortable, streamlined and spacious a 6½-square house can be. As a small nucleus house which you can add to later, or even as a holiday home which can be let for half the year to pay its way, this plan has all the essentials for your first home—a shower room which could have a bath too if you wanted one, a bed-sitting room and a guest bedroom area, a mediumsized kitchen and laundry.

DAY BED - UNIT

DAY BED

DINING & LIVING AREA

The kitchen area has a frig, range and sink with a free-standing table between kitchen and living room. Folding doors, or plantation shutters divide living room from guest bedroom. In the areas where there's plenty of traffic — kitchen, bathroom, laundry, parts of living room, and guest bedroom (which might become a children's room) flooring is of composition tiles. The rest of the living room is carpeted. (This also helps, psychologically, to divide rest area from utility area.) Externally, walls are sheeted with vertical and hori-


zontal boarding. The vertical boarding is stained and the horizontal boarding painted. The skillion roof is of

from the inside by sliding panels at back of louvres.

SHOWER

GUEST AREA 11'X8

Full-Scale Living in



Descriptive Outline

WALLS ROOF

Timber frame, vertical weatherboards.

Low-pitched gable, roofed with corrugated asb. cement or gal. iron.

INTERIORS Walls, fibrous plaster in living and kitchen, softboards and hardboard elsewhere.

AREA

7½ squares.

Colour Suggestion

WALLS

Soft pink.

GABLE ENDS

Deep smokey blue.

TRIM

Grey-blue.

DOOR


Strawberry pink.

EAVES ROOF Ink blue. Grey.

6 PLANS FOR YOUR DREAM HOME


THIS plan combines the ease of operation of a weekend house with all the comfort of a house twice its size! The living room is large enough to hold a grand piano without crowding, yet the architect has still managed to fit in two bedrooms (with ample wardrobes) and as big a kitchen as a 14-square house would normally have. The breakfast bar creates a feeling of informality but this could be balanced by the solidity and dignity of a stone-faced fireplace in the living room. Large plate glass windows open on to the stone-flagged terrace to link indoors with out. This house would not be difficult to extend in the future if more space was needed. Meanwhile for a young family, here's the ideal small home.

This sketch shows hip roof, carport supported by columns, and arrangement of hopper and plate glass windows. Master bedroom has front windows, and there's a side door to carport. See plan.



Variety in 8½ Squares

Architect N. Edwards, A.R.A.I.A. PLAN No. 3



PLAN.1

ARCHITECT Norman Edwards doesn't claim that this 8½ squares plan is original, but one which many homeowners have described as their ideal in economy and efficiency. He does say, however, that a whole street of houses with this plan could be built, each featuring an individual and original appearance. Two of the many variations which could be created on the basic plan are shown here.

Scheme 1 is the more conventional of the two in treatment. It's timber framed with vertical and horizontal exterior weatherboards and a corrugated asbestos cement hip roof.

(Continued on page 58)

Scheme 2 house has adjustable louvre screen in front of sliding glass doors from living room, a different carport — it has asbestos cement roofing and new arrangement of windows. See plan on page 58 for this alternative scheme.

Descriptive Outline

HOUSE NO I

WALLS AREA

Vertical and horizontal boards. Corr. asbestos cement hip roof.

Colour Suggestion

WALLS ROOF

Deep hunter green Off white.


TRIM

White


DOOR EAVES

Flame or natural timber

Nile green.




"Post and Beam" Method Makes Building Economical



THE objective in planning this house was a goodlooking home of two bedrooms which would be suitable as a permanent or holiday house. It is something of a surprise to find that within its 8 squares there is such a large living room and that each bedroom (or bunk-room) has space enough for a walk-in wardrobe. The saving on hall space gives a bigger-than-average kitchen and a family-sized bathroom.

> The kitchenette could be divided from the living room either by heavy draw-drapes or a folding door. The carport serves as an outdoor living area by folding back the large sliding glass sashes in the living room. If wanted, the back wall of the carport could become a storage wall for garden implements.

> The design of this house would be simple for the do-it-yourself home builder to tackle.



Architect, John P. Ley. B.Arch. A.R.A.I.A., A.R.I.B.A. PLAN No. 4

Descriptive Outline

WALLS

Timber frame asbestos

cement sheeting finished with 2" x 1" vertical

battens.

ROOF AREA

Corr. asb. cement 8 squares

Colour Suggestion

WALLS

Deep lavenderbattens white.

ROOF TRIM


Blue-grey. Blue-grey.


DOOR

Deep violet.

EAVES


Lilac.







Swing This Plan to Suit your Site




ALTHOUGH timber is suggested as the exterior material for this smart little 2-bedroom, 81 square home, the plan could very easily be adapted to brick. The design is a very compact one. The exterior treatment is modern. Living and dining rooms are combined, although the

shape makes a definite break between the two areas. It would be simple to enlarge this living room if site and finances permit it. Each bedroom is fitted with a large built-in wardrobe and a roomy dressing table.

14 x12

14'x12'

The plan could be angled to any direction.





Right. Ground floor plan of expanding family home. Ist stage can be without bedroom wing (family room becomes bedroom). 3rd stage shows addition of third bedroom (marked with darkest stipple). Above, on the street side living room wall is of stone with highlight windows. Kitchen wall is of brick. But apart from this interesting use of texture, main house construction is of timber.

A 3-Stage Plan

THIS house has been planned by architect John Parkes for an expanding family and it can be built in three stages. Its plan is especially suitable for a lot in a closely settled suburb where the ground is fairly flat.

These conditions resulted in the following features: The side of the house which faces the street is simple but attractive, and could take up the whole width of the site. The living-dining room and family room (which is the bedroom in Stage 1 of building) open on to a garden

terrace giving the family a good deal of privacy. This can be made complete by the simple addition of a side fence or trellis and short back fence.

BEDROOM 2 12'19

BATHROOM

FAMILY ROOM

DINING AREA

SERVICE

L'DRY

KITCHEN

linen

OUTDOOR

18'0"x 13'6

LIVING

18'x9

FUTURE BEDROOM

There is entry from the outdoor living area to the carport.

The bedrooms, separated from the living area by the family room, overlook the back garden.

The side of the house nearest to neighbours is reserved for the utility rooms and for a small drying area.

(Continued on page 65)

Architect, John Parkes, A.R.A.I.A., A.R.I.B.A. PLAN No. 6

Descriptive Outline

WALLS ROOF AREA

Timber.

Terracotta or cement tiles. 9-15 squares.


Colour Suggestion

WALLS ROOF GABLE ENDS TRIM DOOR


EAVES

Pearl grey. French grey. Deep red. French grey. Ruby red.

White.



view of the house from the private garden terrace. Living room, family room and dining room open out on to terrace. On right are doors of exterior storage wall.



9-Square Plan For Seaside or Suburb

Descriptive Outline

WALLS Asbestos cement or timber.
ROOF Terracotta or cement tile.
9 squares.

Colour Suggestion


WALLS Deep red.
ROOF French grey.
TRIM White.
DOOR White.
EAVES Pearl grey

THIS is a basic plan of 9 squares designed for holiday fun or as a nucleus family home. Ten people can fit comfortably into the house if bunks are double. The living room is 33' 6" long, so there is plenty of room for dancing or games. A slow combustion or a simple fuel stove could be built into the kitchen area.

Bunk rooms can each take four persons. Two more can sleep in the living room. Each bunk room has an outside and inside door. Bathroom has also an inside and outside door to keep sandy feet and wet bathing costumes from the main part of the house.


Construction is of the simplest type . . . exterior could be timber or asbestos cement with roofing of either tiles or asbestos cement. This plan will fit across a 45' block. A skillion roof could be substituted for a gable one.

 $9^{\frac{1}{4}}$ squares



Designed by E. M. Buhrich

For a Block with No View



ALTHOUGH only 9½ squares, this is not a minimum house. The plan allows for an unusually large amount of living area, indoors and out. It is designed for a suburban block without any special view and the best exposure on one side.

The living quarters consist of living room, family room, covered and open terrace and the car port, which can double as a further outdoor living area. The family room is combined with the kitchen but divided from it by a breakfast counter. It takes over the function of the dining and sunroom in the older style of house. It

caters for informal dining, children's play and homework, sewing and general hobbies. It gets the winter sun all day, but is sheltered from the summer sun. Window strips over the sink in the kitchen give light and cross ventilation for the family room and kitchen.

The large living room has windows to the west, and is to be used most often at night. French doors lead from the living room to the terrace so that this room, like every other, has cross ventilation.

A small hall leads to the bedrooms and bath. The (Continued on page 60)

Descriptive Outline

WALLS Part timber, part asb. cement.
ROOF Mineral surface asb. felt over close


boarding. AREA 94 squares.

Colour Suggestion

WALLS Pale grey timber - French grey for

sb. cement sections.

ROOF French grey.
TRIM Charcoal
DOOR Flame
EAVES Pale grey.





"Foldin" doors offer versatility in interior design never before possible. In full colour range of textured Vinyl, "Foldin" doors give new life to your home, add more living area. As a moveable wall "Foldin" divides one room in two. Your solution to growing family problems — a "Foldin" room divider.

UNIQUE HOUSE

139 Boundary Road, Nth. Melbourne, Vic. FY 1381. 83 Buckland Street, Chippendale, N.S.W. MX 4816.


Designed for Spacious Living

"Foldin" concertina type room divisions and doors give you greater use of your present living space.

MAIL	TODAY	FOR	FURTHER
	DET	AILS	

Name	
Address	

COUNTER TOP BASINS



REMEMBER!

1. You pay no more than elsewhere.

2. We maintain our well-known high standard of quality.

3. Our range and display are unequalled anywhere.

... are available in a wide range of colours. Any laminated finish can be supplied, and special units to your own design are readily obtainable. Tap sets extra.

Rogers Seller & Myhill

27 City Road, Melbourne South (opp. Glaciarium). MB 4501



RSM57/DHP8

What you should know about...

FOUNDATIONS

Confidently as building what is commonly termed the foundations. Actually the foundations are the rock or soil formations on which the building is resting. The lowest part of the walls which transfers the weight of the building to the foundations is called a footing. Although the actual work—apart from setting out—does not require much skill, it is most important that this job should be properly understood because a mistake occurring at this stage is almost impossible to correct later on. The consequences of unsatisfactory foundations and footings are, of course, structural cracks which may range from merely unsightly cracks in the plastering to dangerous weaknesses in the structure.


Generally speaking foundations can be one of three

types: rock, sand and gravel, clay.

Rock foundations present the least difficulties. The rock surface has to be scrabbled (chipped) to a true level surface or, where this is simpler to do, it may in parts be built up with concrete to a level surface. This concrete should be no less than two inches thick at any point. The brickwork may then be started with a course $13\frac{1}{2}$ " wide under external walls and 9" wide under

partition walls.

Not everyone is fortunate enough to have rock foundations either at the surface or at a level to which he can dig down. Sand and gravel are hard, gritty materials (the difference between the two is the size of the particle) that have no cohesion, or in other words, do not stick together like clay particles. For this material it is necessary to dig trenches down to a depth of twelve or eighteen inches. In N.S.W. building regulations require the width of footings to be twice the thickness of walls above, that is 22" for 11" cavity walls and 9" for 4½" walls and the height to be 9". For practical reasons footings under 4½" walls are frequently wider than this.




Above left. Concrete reinforced with steel rods. Above right. Brickwork below ground level built into cement.

Commonly these footings are built in reinforced concrete. The concrete is mixed to the proportion of one part of Portland cement to two parts of sand to four parts of blue metal or other suitable aggregate. The concrete must be reinforced with four or six §" diameter



steel rods which must be placed in two layers, one 2" down from the top and one 2" up from the bottom of the footing. This 2" concrete cover is designed to protect the steel from rusting, hence the same distance must be kept at the sides also. Where the footing is stepped (which it must be unless the ground is level) the steel rods should be bent to a slope of one in six or lapped 2 to 3 feet. The steel rods are kept in position by so-called ligatures, 4" diameter rods which are bent to something like a U-shape and spaced approximately two feet. Black wire is used to tie the rods to the ligatures.



Above right. Brick piers must be topped with ant caps.

Left. Special footing for difficult foundation.


These footings are designed to carry the weight of the walls above. If, instead of a wall, a large door or window occurs it is quite conceivable that the footing bends upwards. Cracks will then show next to the opening. To avoid this danger ½" diameter rods are placed on top of the footing under all large openings. These rods are additional to the ones mentioned before and are also placed two inches away from the edge of the concrete.

Brick or stones may be used for footings instead of concrete. Brickwork should be started with two courses 23" wide and stepped up with two 18" and two 13½" courses to the 11" wall. All brickwork below ground level should be built in cement mortar, that is mortar mixed of one part of cement to three parts of sand with one tenth part of lime added because it makes the mortar more workable. (Continued on page 55)

A Gem of a House in Vertical Timber

COVER HOUSE

PLAN No. 9



VOU get a lot of living in this 9½-square timber home. It has a convenient and adaptable layout for a young family. It is planned for easy maintenance. The denguest room could become a third bedroom or a separate alcove for TV showing. The living room lends itself to good decoration with central fireplace and dining.

The house is framed in timber with a slightly pitched


roof covered in asbestos cement. The screen-fence is not essential, but if the house is built in a closely settled suburb it would give privacy to outdoor living at the side of the house. Note how plumbing is grouped for economical installation. The laundry could incorporate a sewing corner as well.

Descriptive Outline WALLS 6" x 1" timber

ROOF Corr. asb. cement AREA 9½-squares.


Colour Suggestion

WALLS Ink blue, ROOF French grey TRIM White DOOR Bright Pink EAVES Pale Grey.




How to have a genuine TILED BATHROOM in your timber framed home....





Send to-day for more detailed information on how you can use Lysaght METALATH in your home. Fill in and post the coupon now.

Available in sheets 2' 3" wide and 8' and 9' in length. Price (Australian Capital Cities) 5/3d. per sq. yd. (Full sheets).



Building or renovating a timber-framed home? If so, you can still have a beautiful ceramic tiled bathroom and kitchen . . . or have any interior or exterior wall finished in plaster or cement render in the modern manner. Simply ask your builder or architect to specify Lysaght METALATH.

Made by slitting and stretching steel sheet into a network of diamond-shaped meshes, it is nailed to the studding and provides a perfect key for the cement. Tiles are simply affixed in the normal manner. The finished wall is of great strength—identical in appearance and durability with those found in brick homes.

LYSAGHT METALATH

John Lysaght	(Aust.	Pty.	Ltd.,	Sydney	Brisbar	ne, h	delbourne,
Adelaide and	Freme	intle.	or L	ysaght's	Works	Pty	. Limited,
Newcastle, N.	S.W.					70 V 7	
John Lysaght	(New	Zeala	nd) L	imited,	Welling	lon,	Auckland,
Christehurch.							


Please send me, without obligation, tull details on the use of Lysaght Metalath in timber framed homes.

NAME			
ADDRESS	 	 	

D.H.

10 squares

Realistic Plan



is Budget Beater

HERE'S a three-bedroom house in an area of only 1070 square feet (excluding the carport) . . . a wonderful little family house which could be built either in timber or asbestos cement. The site for this design could be either flat or slightly sloping. A 45' block would be adequate for it.


The carport is connected to the house by a pergola which also provides a sheltered porch at the entrance door.


Living-dining room is open planned with sliding or French doors leading to a flagged terrace. The hearth is at an angle. There is a fuel box next to the fireplace. The entry itself is given privacy from the rest of the living room by a floor-to-ceiling divider.

Each bedroom has its own built-in wardrobe. There are two linen cupboards in the house. The separate


toilet has a hand-basin.

Foundations could be either brick or stone. The skillion roof could be built-up roofing or aluminium. If preferred, the roof design could be changed to a low pitched gable ... it would not detract from the look of the house.





A Home with a Verandah




TWO grand features now almost forgotten in suburban homes . . . a verandah and a pantry . . . are incorporated in this 10-square timber home. It would make a wonderful country house or farm homestead. With a homestead in mind, our architect has proposed that bedroom 2 becomes the office of the future (so necessary for the business side of farm life). The perfect aspect for the verandah (an extra 3.8 squares) would be to the north. Nor does the verandah darken the rooms opening on to it. They all have windows in the outside walls as well. Windows on the northern and western walls are further protected by louvred shutters.

In the country, with no little shop around the corner, it is necessary to have extra bulk-storage space. This plan has a well-ventilated pantry and room in it for a


deep freeze unit as well as a refrigerator. Another feature is the covered way which could incorporate a cupboard for storing wet-weather coats, etc. The sheltered courtyard makes a delightful place for growing vegetables and herbs close to the kitchen.

Exterior is timber with a tiled or corrrugated asbestos cement roof. Eaves are much wider than usual.









Appealing Plan has Alternative Treatment

Architect, John P. Ley, B.Arch. A.R.A.I.A., A.R.I.B.A. PLAN No. 12



Descriptive Outline

WALLS ROOF **PANELS** AREA

Natural cypress boarding. Corr. asbestos cement. Asb. cement (striated or plain)

10½-squares.

Colour Suggestion

WALLS ROOF TRIM


Natural timber. Left natural. White.


PANELS DOOR Royal blue or jade green.


Deep red. EAVES White.

THIS small brick house of 10½ squares presents a solid yet smoothly designed facade to the street. The floor plan is a good one for such a minimum home. Bedrooms are a comfortable size, but the biggest attractions are the very large living room, the separate dining room, and the "U"-shaped kitchen. An attractive screen or a floor-to-ceiling cupboard with buffet combined could divide dining and living room.

Our architect has given an alternative elevation for those homemakers who prefer a very modern exterior. This roof line, combined with a panel of vertical stained boarding, makes it an entirely different house.







Cut your roofing costs as much as 30%...with

LYSAGHT

GALVANIZED

To-day's trends in roof design—skillion, flat and butterfly — are "made to order" for the skilful use of Lysaght Galvanized Steel Sheet.

Available both flat and corrugated, this versatile roofing material blends into any modern home plan. And because of its enormous tensile strength, you can rely on it to give a lifetime of service with normal care and maintenance.

By specifying Lysaght Steel Sheet, you immediately cut your roofing costs, too! Compared with other roofing materials, Lysaght Steel Sheet can mean a saving of from 15% to 30%!

Why not discuss the many cost-saving advantages of using Lysaght Galvanized Steel Sheet with your architect or builder to-day?

John Lysaght (Australia) Pty. Ltd.
Offices in all Capital Cities





ROOFING SHEETS—THESE SIZES AND GAUGES AVAILABLE Lengths of 5' to 12' (1 foot increments) 12 x 3" Corrugations — 26 gauge 8 x 3" Corrugations — 22, 24 and 26 gauges 10 x 3" Corrugations —

22 and 24 gauges
5 x 5" Corrugations —
14, 16, 18 and 20 gauges
Lengths of 5' to 10' (1 foot increments)
25 x 1" Corrugations —

25 x 1" Corrugations — 26 gauge Lengths of 6' and 8' Flat sheets — 16, 18, 20, 22, 24 and 26 gauges

G106B

What you should know about...

ROOFING


NO building is so dependent on a single factor for its appearance as on the type of roof used. Indeed we almost identify architectural styles by roof shapes such as the steep gabled roof being Tudor or the flat roof, modern. This, like most generalisations, is inaccurate. But nevertheless it is the roof shape that gives a house its characteristic appearance.

Originally these shapes evolved from construction methods and available materials, but in time the procedure has become reversed; the roof shape is chosen for other reasons, mostly aesthetic, and materials and construction methods are found to fit this pre-

conception.

However, the roof has other and more important functions to fulfil: it is the main surface exposed to the weather and shelters the house from heat and cold, from snow and rain. Waterproofing is, then, one of the main considerations when designing a roof and all its details and some measure of insulation is another one.

Roof shapes like many other features have been simplified in contemporary buildings. No longer is a house considered undignified unless it has innumerable gables, hips, valleys and dormers at various levels. This desire for plain geometric shapes may have led the early contemporary designers to use the flat roof so extensively and without considering other aspects.



Moreover, the flat roof is by no means flat, but is just any roof of low pitch hidden behind parapet walls. This type of construction presents particular problems in waterproofing, which have done much to discredit it.

But before considering this type of roof any further, let us see what other

shapes there are.

All over the world and over a period of centuries the gable roof can be found as a simple solution to covering the small house. The ridge runs parallel to two (usually the long) walls and two inclined

surfaces produce the triangular gable shape where they intersect the end walls.

The name, gable roof, refers to the shape, not as some people think to the pitch, and a gable roof can be as low-pitched as its covering

material will permit.

In the hipped roof, the end surfaces are not vertical as the gables but inclined at the same pitch as the two main areas and the eaves line continues around the whole house. In special cases all roof surfaces come to a point over the centre of a square house, but more commonly a longer or shorter ridge runs parallel to the long walls. The hip roof is of advantage where water collection is a problem because all the roof water can be collected at one point.

Where the plan shape is anything but a plain rectangle a combination of hips and valleys and/or gables is needed and this is what produces the effect of heaviness or fussiness that we often find in small suburban houses. One way of overcoming it is to vary the roof overhang so that



a simpler roof shape may cover a more complicated plan shape. Another is to simplify the plan itself.

The skillion or single-pitch roof has an undeservedly bad reputation. Some call it a lean-to and associate it with cow sheds and fowl houses. It can be a very pleasing and particularly economic shape for a small house that presents few problems of construction and waterproofing. application makes it possible to get extra height into big living rooms and use lower ceiling heights, say, for a small bathroom, an advantage, however, that cannot always be realised where a minimum ceiling height of nine feet is prescribed. The skillion roof allows for additional ventilation of rooms or the roof space but shading of windows through roof overhangs may become a problem.

The butterfly roof has now become well known in Australia. The two roof surfaces are inclined inwards so that the lowest line, the gutter, runs across the centre of the house. Although we might not advocate its adoption indiscriminately, it is very useful where additional light or ventilation is needed in the centre of a house. Since all rainwater runs towards the centre, care must be taken in waterproofing the butterfly roof.

These are the main roof shapes that we find on small houses today. Others, like the mansard roof, are no longer much used.

Roof construction may be in either timber, steel or concrete and a variety of covering materials are available.

Traditional timber construction employs a number of straight timbers, such as rafters, purlins, struts, hips, hangers, etc., which are housed into each other and nailed together. Most houses in Australia are roofed in this manner and building regulations prescribe minimum sizes for these timbers. This construction has been developed over many years and is certainly strong enough if not particularly economic.



In a number of prefabricated houses, engineering principles are applied to roof construction and a timber roof truss is used that is designed properly for the stresses that occur. This construction is far more economical both in the use of timber and labour but cannot, at present, be employed by the individual home owner.


Steel construction is rarely applied in house building in Australia though light steel trusses are sometimes used and could be used more often.




Reinforced concrete is commonly used for flat roof construction where the roof is intended as a deck, although it must not be forgotten that a flat roof can be constructed economically in timber.

A concrete slab is usually about four or five inches thick and reinforced with steel rods. It must be calculated by an engineer. A number of layers have to be added to make the roof complete.

(Continued on page 58)





Descriptive Outline

WALLS ROOF AREA

Timber.
Terracotta or cement tiles.


10-squares.

Colour Suggestion


White.

WALLS ROOF GABLE ENDS TRIM DOOR EAVES Terracotta.
Royal blue.
Royal blue.
Black.
Mid-blue.

Architect, Viwa Turner PLAN No. 13







No Waste Space

Descriptive Outline

WALLS BATTENS AREA

Asbestos cement. Corrugated Asb. cement. 2" x 1" timber vertically. 10-squares.

Colour Suggestion


EXTERIOR WALLS TRIM DOORS ROOF

EAVES

Grey green. Mushroom pink. Grey green. Bright pink.

in 10-Square

IT'S hard to realise that there are three bedrooms behind this pleasing facade. In spite of its minimum area of 10 squares this house has space for a terrace with direct access from the living room and an imposing book-flanked fireplace in the cosy living room. The lobby has its own coat cupboard and is divided from the dining room by a floor-to-ceiling wrought iron screen.




Architect, John P. Ley, B.Arch, A.R.A.I.A., A.R.I.B.A. PLAN No. 14


Home


As this home is planned for a family the laundry is large and equipped with a drop-down ironing board.

There would be room here for a linen cupboard.

The exterior is asbestos cement with 2" x 1" timber battens set vertically on the flat asbestos sheets—giving the appearance of "board and batten" treatment. The roof is of asbestos cement, also with wide corrugations.







The front entrance is reached by a ramp (either concrete or timber) which runs along the side of the

Exterior walls are sheeted vertically with 4" x 1" Vjointed mahogany boarding. Foundation walling is of colour-washed brickwork. The roof is covered with mineral surface asbestos felt on close boarding.

Architect, John P. Ley, B.Arch., A.R.A.I.A., A.R.I.B.A. PLAN No. 15

Descriptive Outline

ROOF

WALLS Mahogany boarding (4" x 1").
FOUNDATIONS Colour-washed brickwork.


Mineral surface asb. felt on close

boarding. AREA 11-squares.

Colour Suggestion

WALLS Natural finish. FOUNDATIONS Sage green. TRIM Sage green. DOOR Peacock green. EAVES Lime yellow.

Traditional Look—



A CONTEMPORARY version of the American ranchstyle house fits very well into the Australian countryside. This one, only $11\frac{1}{2}$ squares, has a beautiful floor plan . . . one of the most flexible and efficient livingkitchen arrangements we've seen. It manages to fit three bedrooms into the fairly small floor area.

The unusual entrance courtyard is punctuated by oddshaped planting areas which give extra glamour to the external appearance of the house.

Another fine feature is the entrance hall with its 6' 8" high storage wall which takes coats and out-of-season equipment. The screen behind the planter could be in light glazing or airy wrought iron.

A servery with sliding doors (next to the refrigerator) connects kitchen-dining area, and note the little separate phone bureau in this room.

Exterior-wise, horizontal 6" x 1" splay-cut weather-boards pleasantly contrast against the bar-divided windows and tile roof.




WALLS
GABLE ENDS
Timber or asb. cement.

ROOF
AREA


6" x 1" splay-cut weatherboards.
Timber or asb. cement.
Terracotta or cement tiles.

Colour Suggestion

WALLS
ROOF
GABLE ENDS
TRIM
DOOR
EAVES
Cocoa brown,
Pale grey,
Pale tangerine.
White.
Bright tangerine.
White.



Modern Workability



Building or Renovating?



ALSYNITE admits daylight freely, providing a soft, natural diffused illumination free from shadows and glare, yet complete privacy is assured with these colourful translucent fibreglass panels. ALSYNITE can be adapted for roofs, skylights, side walls, windows, awnings, sunrooms, car ports, partitions and innumerable other uses.

COLOURS: Clear (natural colour), Leaf Green, Light Green, Maize, Moonglow and Opal Blue.

TRANSLUCENT: Privacy with maximum light . . . diffused, shadowless,

SHATTERPROOF: Will not crack, craze, warp, sag, buckle, rot or mildew.

VERSATILE: Solves hundreds of building and designing problems. Adds a distinctive charm . . . new VERSATILE:

and different beauty . . . at low cost.

LENGTHS: 6, 7, 8, 9 and 10 feet.

WIDTHS: 26 ins. (8-3 in. corruga-tions), 32 ins. (10-3 in. corrugations).

Also available in deep-six corruga-tions to match asbestos cement sheeting profiles.

NEW SOUTH WALES DISTRIBUTORS:

Cheapa Glass Co. Ltd., 107 Parramatta Rd., Camperdown—LA 5119. James Sandy Pty. Ltd., Boronia St., Redfern — MX 5451. Sydney Glass Co. Pty. Ltd., 578 Prince's H'way, St. Peters—LA 6151.


Marketed exclusively throughout Australia by AUSTRALIAN WINDOW GLASS PTY. LTD.


(Branches in all States)

Do it yourself with



THE ORIGINAL TRANSLUCENT FIBREGLASS BUILDING PANEL





What you should know about...

White-Ant Proofing

WHITE ants attack buildings in all Australian States. Prevention is cheaper, and more effective than cure The termites attack structural timber from underground nests via foraging galleries (eathern shelter tubes) which they build over brickwork, concrete, durable or creosoted wooden house-stumps, etc., to make contact with more suitable food material, perhaps many feet above ground.

A turned-down sheet of metal prevents termites building their galleries from a stump or wall on to structural timber.

Buildings of concrete, brick, brick veneer or timber should be fitted with shields or caps made of 24 or 26 gauge galvanised iron or copper the outer 2 inches of which should be turned down at an angle of 45°. The metal should project at least ½ in. before turning down. Where strip shields joint at wall junctions, joints should be soldered with a lap of at least 1 in. Galvanised iron shields should be laid on a damp-proof course. Sheet copper can serve both as ant-capping and damp-proof course.

Debris, mortar, or timber should not be left under a building to provide access over the metal shield to the timbers above. Ventilation and air circulation under all floors is essential; a minimum ground clearance of 18 ins. is desirable. Drainage should be efficient, as moisture attracts

- joist bearer cap 18"minimum around level TERMITE CAP FITTED TO A BRICK PIER

Chearer -termite cop tar and 1/2 bolt cast pitch or in concrete cement mortar

TERMITE CAP FITTED TO 4 CONCRETE PIER

Fitting Termite Shields and Caps

Walls-to prevent corrosion, shields are placed directly on the damp-proof course. The plate or bearer and brickwork are laid on the shield, and, in order to prevent sliding, the top surface is given a thin layer of tar and sand or bituminous paint. Do not damage cap while fixing, or (Continued on page 66) perforate it with nail holes.





FORMINEX is a pure plastic — a miracle of modern science. It brushes on easily, smoothly for a brilliant gloss, extremely hard finish that lasts for years. And if you get grease, oil, household chemicals or boiling water on FORMINEX you just WIPE or SCRUB it off . . it's hard to damage that amazing FORMINEX surface.

CLEAR FORMINEX used on exterior weatherboards, floors, furniture, gives a hand-polished appearance which accentuates the natural wood grain—magnificent. Full-color FORMINEX on concrete paths, fibro, baths, cupboards, built-ins — anything — will delight you. You get bonus benefit from FORMINEX: save time, work and money as it lasts for years. No special sealers are required and one gallon covers 750 to 1,000 sq. ft.

DECORATE AS YOU PROTECT. DECORATE AS YOU PROTECT.

FORMINEX PROPRIETARY LIMITED DISTRIBUTORS IN ALL STATES

ASK FOR THE FREE FOLDERS AT YOUR STORE

NOW - discover

Hotpoint


cooking speed, operating economy

for yourself ...




DUAL PURPOSE HOTPLATE ... Separate Grilling Compartment

Instant-heating Hotplate reaches cooking temperature in seconds. There's room for three or four saucepans on top . . . grill beneath at the same time. That's real Hotpoint *speed* and *economy*.




Quick-heating and so easy to clean, new AEI Hi-Speed radiant elements reach cooking heat in seconds, glow red-hot, cook faster than ever. Special spill-pans lift out for each cleaning.



(1)

AO - LHGWMH4 bUT HELW CPOHB of 2 STAOW 4 BE 5 SINV

16 Modern Electric Ranges Ablaze with New Features, Convenience, Beauty . . .



RD4 De Luxe features:

Master oven with automatic time control clock -Speed heating utility oven griller — Automatic temperature controls and interior lights — Four AEI Hi-Speed Hotplates — Automatic clock — Oven and minute timers.

HOTPOINT DIMENSIONS & **SPECIFICATIONS**

I. RD4 DE-LUXE RANGE

Hotplates: AEI Hi-Speed radiant type: 2 = 64 diam. 1250 watts. 2 = 8 diam. 2050

Master Oven: Overall, 15% wide x 15% high x 19" deep. Working space, 15% wide x 14% high x 19" deep. Top element 750 watts, bottom element 2300 watts.

Utility Speed Oven: Overall, 13\frac{x}{8}" high x 15\frac{x}{1}" wide x 19" deep. Working space, 12\frac{x}{8}" high x 15\frac{x}{3}" wide x 19" deep. Top and bottom elements total 3.9 kW.

Wiring: 3-phase and neutral connection. Max.

consumption (includes 10 amps. for power point), 14.5 kW. Overall Dimensions: Height splash back, $46\frac{7}{8}$ ", Height hob, $36\frac{1}{4}$ ", Width 39", Depth front to back 26", including handles $27\frac{3}{4}$ ", with doors open $44\frac{1}{2}$ ".

2. and 3. RE3T AUTOMATIC ELEVATED Same electrical specification as RA3, plus automatic timing device and electric clock.


automatic timing device and electric clock. Overall dimensions on cupboard base or legs: Width 48", Depth 19½", height to top of oven 47¾". Height to top of hob, 32½". Without top of hob 8½".

5. RE3/H HOB UNIT

Same as Hotplate and griller section of RE3T.

Max. consumption 5.7 kW. Overall Dimensions:

Width 24". Height 8\frac{4}{4}". Depth 19\frac{1}{4}".



RE3T automatic elevated range

Thermostat control for constant heat — Automatic time control clock for oven — Three AEI Hi-Speed Hotplates — Separate compartment with griller/boiler element — Choice of style. Left or right hand oven.

. 6. RE3/OT OVEN

Same as oven section of RE3T. consumption 2.2 kW.

Overall dimensions—Width 24". Height 24".

Depth 194". 7. 8. and 9. RE3 ELEVATED

Oven and Hob — same specification as RA3. Overall Dimensions: Width 48". Depth 19½". Height — 42¾" to top of oven, 36" to top of hob.

10. to 13. RA3 THREE-PLATE "BALLERINA" MODELS

"BALLERINA" MODELS

Hotplates: AEI Hi-Speed radiant type: 1 = 8"
diam. 2050 watts. 1 = 64" diam. 1250 watts.
1 = 10" x 8" 2400 watts. Griller/boiler.
Oven: Overall 19" wide x 12" high x 15" deep.
Working size 19" wide x 114" high x 14"
deep. Bottom elements 2200 watts.
Dimensions overall: Width 24", Depth 194".
Hob height on stand 36". Height without stand 22½

Wiring: 2-phase and neutral connection. (Max. consumption 7.9 kW.)

14. to 17. RA2 2-PLATE "BALLERINA" MODELS

Hotplates: AEI Hi-Speed radiant type: 1 = 8" diam. 2050 watts. 1 = 9" x 7" griller/boiler element 1750 watts.

Oven: Same specifications as RA3. Wiring: 2-phase with neutral connection. Max. consumption 5.75 kW.

Overall dimensions: Same as RA3. Note. Due to constant improvement in design the specifications are subject to change without notice.



RE3T separate units

(5

"Special" individual units for built-in

styling

6



Hotpoint

makes cooking a pleasure so quick - so simple, too!


Here are the fast, automatic, economical electric ranges that every housewife wants. They know that Hotpoint was the first to make an electric range, and through the years, every worthwhile feature has been added. The Hotpoint range of today reduces cooking time increases cooking pleasure. Its fast, clean, heating action and convenience makes meal times much more pleasurable. As well as the practical aspects of design, Hotpoint ranges are planned with an eye to beauty and versatility, too. No matter what your cooking needs may be, there's a Hotpoint range to give the features you want in a style to blend with your kitchen setting.



element — great power economy. aluminium grill-pan with insulated handle supplied, also griddle plate.



Inset grouped controls are at convenient height. "Simmerstat" gives infinite range of heat for simmering or fast boiling. Oven control clearly marked in degrees — simply turn to heat required — and it automatically maintains correct temperature.




Smart, fluted handles, both oven and griller compartment doors are sprung-counter-balanced and fitted with easy-grip, chrome-plated, solid brass handles. Extra width of handles is handsome and useful, no grease-catching crevices. Oven vents are cleverly concealed in ends of handle.

Guaranteed by:

AUSTRALIAN ELECTRICAL INDUSTRIES

LIMITED

Obtainable from electricity supply authorities and Hotpoint retailers everywhere.



What you should know about...

HOME LIGHTING

IT is only in the last few decades that artificial illumination was studied scientifically. Although this study was directed towards industry and schools rather than the home and although it is still by no means conclusive, yet there is enough knowledge now to apply to our homes the best that industry has to offer.

When planning the various light sources and fittings we must consider three questions:

1. The Kind of Light

There are many possibilities such as direct light with sharp contrasts and deep shadows; soft and diffused light; light reflected from the ceiling thus providing overall illumination with very little shadow; directional light by such devices as louvres or prismatic lenses; localised light of which a particularly good example is the Illuminating Engineering Society's Better Light—Better Sight lamp which is generally recommended by lighting authorities. Then there is colour light to be considered

and, although one should be wary of introducing coloured incandescent light, one of the several available colours (from peach to daylight) must be chosen for fluorescent light and should be considered together with the colour scheme of the room.

2. The Amount of Light

Our eye is a remarkable instrument which is quite capable of adjusting itself to brightness which may vary from 1,000,000 (for white areas in direct sunlight) to 1. It is therefore unlikely that for normal healthy people you will get too much light. It is, however, quite possible to get brightness contrasts of such intensity as to be harmful (glare). The amount of light is reduced by any decorative fitting, the reduction depending on the density of the material used for shades. It is also reduced at the rate of the square of the distance, in other words: by coming three feet closer to a light source your brightness will increase nine KEY TO LIGHTING PLAN

STABLE LAMP & POWER POINT OCEILING OUTLET & REFRIGERATOR OWALL BRACKET & RANGE SINGLE SWITCH S2 2-WAY SWITCH

3. The Position of the Light

This should be self-evident when consideration has been given to elimination of glare and to the seeing task involved.

One particularly hard rooted idea is to have a centre fitting under all circumstances. Although centre fittings are comparatively cheap to instal and have their uses in certain positions they are not usually the best solution of a lighting problem in living rooms. Besides there is still a shortage of well-designed ceiling fittings on the Australian market and concealed fittings or mobile lamps frequently are the better answer.


To give more specific solutions to lighting problems we are showing the plan of an average suburban cottage and discussing its various lighting questions.


A. OUTSIDE: This part of home lighting is often neglected. Outside lighting for safety is a matter of course.

(Continued on page 64)



Brick Modern





Descriptive Outline

WALLS

Asb. felt with mineral surface finished fixed to close boarding.

AREA

114-squares.

Colour Suggestion

Cornflower blue.

ROOF TRIM DOOR Pale grey. White. Rose pink. Pastel blue.

will give you life-long comfort

Architect, John P. Ley, B.Arch., A.R.A.I.A., A.R.I.B.A. PLAN No. 18

THERE are many times when a block, for the sake of building economy, demands a split-level design. This plan could be the answer if your block slopes from front to back.

Two good-sized bedrooms fit into the design of 1,127 square feet. The dining corner is the "L" of the living room floor space. Dining section is open to the kitchen. Kitchen is completely hidden from the living room. No fireplace is shown but if one was wanted it could be included in the wall with the kitchen behind it.


A small flat hood projects over the front entry door and is carried inside the house to provide concealed lighting and to reduce the apparent height of the ceiling at this


point.

Bedrooms are grouped with the bathroom on the higher level. Living-dining-kitchen and laundry are placed on the ground level. A small two-way cupboard between stair landing and laundry provides storage for soiled clothes—no

running around on washing day!

The house is built in colour-washed brick with a skillion roof running down over the two levels. Roof is asbestos felt with a mineral surface finish fixed to close boarding. The face of the exterior flower-box is tiled with terra-cotta paving tiles.





First-Rate Design

bas exciting features...

THIS house with an expanding living room has an area of 1176 sq. ft. It is constructed in timber frame with vertical "V" jointed T. and G. boarding as an external sheathing material.


The bedroom wing is separated from the kitchen and dining room by the living room. At each end of the living room a folding glass wall opens on to a courtyard. For summer living the glass walls fold away to increase the living room length from 23' 0" to an overall 42' 0", including the courtyards.


A 6' 0" high brush fence surrounding each courtyard

gives complete privacy to the whole indoor or outdoor living area.


An eastern-style ornamental screen separates entry from dining. The planting box inside the entry serves as a living room division. The built-in sideboard, under the dining room windows, provides storage space for all dining requisites and cutlery. The storage wall in the lounge houses cocktail bar, TV area, radiogram and bookcases.

The floor is a concrete slab which provides continuity between courtyard and living room floors.






FRONT ELEVATION




SIDE ELEVATION

Architect, John P. Ley, B.Arch., A.R.A.I.A., A.R.I.B.A. PLAN No. 19




A Small Colonial House...


that's really long-lined and elegant!




IF we were asked to choose the type of house which has the greatest national appeal, we would name the Cape Cod or Colonial design without hesitation. The long graceful lines of the Colonial house make it part of the land it is built on. It is easy to imagine green lawns sweeping right up to the house. We think in terms of cool shuttered windows, spacious rooms and complete privacy the minute we think of this kind of house. The

design adapts itself wonderfully to modern living by adding larger windows than are usually used on the traditional Colonial version. The windows could very simply be French doors opening out on to a wide terrace with a pergola over it. We see this particular house in shades of pastel pink walls, deep lilac shutters, tiles of deep blue, delphinium blue door and eaves . . . and if there is a pergola, with a wisteria climbing over it!





Architect, W. Watson Sharp, F.R.A.I.A. PLAN No. 20




Descriptive Outline

WALLS ROOF AREA Texture or common brick painted Tile or corr. asbestos cement 12-squares.

Colour Suggestion

WALLS
TRIM
SHUTTERS
DOOR
ROOF
EAVES
Deep lilac.
Delphinium blue.
Deep smokey blue.
Delphinium blue.

HAPPY HEALTHY HOMES ARE WEIGHTE HOMES



* Installs in Rooms with or without Fireplaces

Designed for YOUR home . . . New or Old

- TRIPLE PURPOSE
- SLOW COMBUSTION
- AIR CONDITIONING

Home builders can save the cost of a fireplace and enjoy the cosy warmth and comfort of an open fire by installing a Warmray Model No. 2A triple-purpose, air-conditioning, slow-combustion room heater.

Yes! The Warmray Model No. 2A capacity 5000 cubic feet, actually circulates warm air to every part of the room—no need to hug the fireplace. No costly installation—no mess—no fuss—burns all solid fuels, and what a saving on those fuel bills. If you are looking for a dependable all-Australian, slow-combustion heater that lends charm and cleanliness to the home, then contact your local Warmray Agents or Warmray Pty. Ltd., direct for name of your nearest retailer.


Owing to fuel saving, the "Warmray"
ACTUALLY COSTS NOTHING

MODELS TO SUIT ALL HOMES.
SIMPLE, POSITIVE OPERATION.
NO "FANS" OR GADGETS TO CAUSE
TROUBLE OR EXPENSE.
NO FRAGILE EXPENSIVE GLASS DOOR
PANELS TO SHATTER.



* BEWARE OF IMITATIONS!

WORLD
PATENTED HEATING TUBES MAKE
THIS THE MOST
ECONOMICAL
AND BEST ROOM
HEATER OF THEM
ALL — REGARDLESS OF PRICE!



- * Lights in seconds
- ★ Warms entire room in minutes with "background" warmth for adjoining rooms
- * Excellent for drying clothes
- * Safe for children
- * Burns all solid fuels. Wood is cleanest
- Colour styled to harmonise with all furnishings
- ★ Gleaming vitreous enamel on solid cast iron

WARMRAY PTY. LTD.

Manufacturers and Wholesale Distributors: Challis House, Martin Place, Sydney. Telegrams: "Warmray". BL 2217
If unobtainable locally, phone, write or call for illustrated Brochure and name of nearest agent.
SOLD BY STORES, BUILDERS' SUPPLIERS AND HARDWARE MERCHANTS EVERYWHERE

NOTHING EQUALS WARMRAY'S AMAZING EFFICIENCY

Distinctive 2-Storey House

A TWO-STOREY house appeals to many people. A clever plan like this one results in an impressive home achieved with only a limited budget. The area is 12 squares.

Lobby has a smart stone planting box, big storage cupboard and cloakroom with downstairs toilet.

First floor is asbestos cement sheets with 2" x 1" timber battens fixed vertically at 9" centres. Ground floor is colourwashed brick.

Descriptive Outline

WALLS Ground floor-colour washed brick.

First floor-asb. cement.

ROOF Terracotta or cement tiles. AREA 12-squares.

Colour Suggestion


(Ground floor) French grey. (First floor) Dusty pink. Infill panels—strong grey. WALLS


ROOF Pale grey.

Pearl grey. Deep lavender. TRIM DOOR


EAVES


Soft pink.





Architect, John P. Ley, B.Arch. A.R.A.I.A., A.R.I.B.A. PLAN No. 21






Simplified Plan Suits 40' to 60' block


PLANNED so that it could be placed in alternative ways to suit a narrow or a wide block, this two-bedroom, 12-square house deserves your attention. It makes clever use of existing space. The fireplace wall has been used to supply a wardrobe, linen cupboard and

coat cupboard. Another pleasing feature is the in-built floor-to-ceiling shelf for books in the living room.

The dining room, kitchen and living room flow into each other with only the partial division of the projecting kitchen wall and open breakfast bar.











today's best way of building!







Hardie's 'Fibrolite' is the most versatile building material of all. Conventional or contemporary, large home or small . . . lower costs mean more home . . . more luxury living area for your money when you build with easy-to-erect, economical 'Fibrolite' Asbestos Cement sheets. Fire retardant, white ant and borer proof, 'Fibrolite' will not warp or buckle, cannot rot of decay. You may paint 'Fibrolite' as colourfully as you wish—but you paint to decorate, not to preserve.

There's a large, labour-saving 'Fibrolite' sheet for every purpose . . . Flat sheets for exterior walls and smooth contemporary interior walls and ceilings, gable ends, eaves soffits . . . textured Striated sheets for distinctive internal and external feature walls and panels . . . smooth-surfaced, colourful, marble-finished 'Tilux' panels bring charm and personality to kitchen and bathroom . . rustproof New Contour Corrugated sheets for attractive, durable roofs, together with a complete range of accessories including gutters, downpipes, ridging, etc. Not only does a 'Fibrolite' home cost less to build, but less to maintain, less to insure.

HARDIE'S

Send coupon to-day for free and post-free illustrated book of contemporary home plans . . . learn how you can have a superior home . . . a new design for luxury living, when you plan and build with Hardie's 'Fibrolite.'

FLAT, CORRUGATED & STRIATED ASBESTOS CEMENT AND 'TILUX' WALL SHEETS PANELS

Sole Manufacturers:


JAMES HARDIE & COY.

SYDNEY: Cnr. York and Barrack Streets.
NEWCASTLE: 324-326 King Street.
MELBOURNE: Cnr. City Road and Clarendon Street.
BRISBANE: Breakfast Creek Road, Newstead.
PERTH: Welshpool, Western Australia.
ADELAIDE: (Known as As




7	Please send me free and post-free illustrated book of contemporary 'Fibrolite' home plans.
	NAME
	ADDRESS.
	НМ3

Comfort and lifetime Protection



start right with Sisalkraft for weatherproofing and insulation



and protection with Sisalkraft — the tough, waterproof sisal-reinforced paper. Use Sisalkraft for wall sheathing, and roof sarking for complete protection against dust, draughts and weather damage. With Sisalkraft Foil Sisalation, which is Sisalkraft double coated with aluminium foil, you obtain complete protection as well as reflective insulation — keeping homes cooler in summer,

Irrespective of the type or size of home you plan, you'll be wise to discuss the use of Sisalkraft with your architect and builder. It's daily becoming an inexpensive building "must".

Learn more about Sisalkraft and its 1001 uses round the home and for home building and protection by sending for free detailed literature — it will be well worth your while. Write now!

SISALKRAFT

aluminium foil

Available at all leading city, suburban and country stores.

NEW SOUTH WALES Sisalkraft Distributors Pty. Ltd., Arthur St., Homebush. Telephone UM 5231 (10 lines).


VICTORIA Sisalkraft Distributors Co. Pty. Ltd., 152 Miller Street, West Melbourne. Telephone FY 1291.


QUEENSLAND Sisalkraft Distributors Pty. Ltd., 23 Ross St., Newstead, Brisbane. Telephone L 3357.

SOUTH AUSTRALIA Sisalkraft Distributors Pty. Ltd., Torrens Road, Goodall Avenue, Challa Gardens, Adelaide. Telephone JL 5353.

WESTERN AUSTRALIA Sisalkraft Distributors Pty. Ltd., (formerly Aust. Reinforced Paper Co.), "Tedco" House, 79 Stirling St., Perth. Telephone BW 1778.


A Plan to Satisfy Most Family Needs






12 squares

Architect, W. Watson Sharp, F.R.A.I.A. PLAN No. 24







A Little

Beauty for a

Narrow Lot





Descriptive Outline

WALLS INTERIORS AREA

Timber or asbestos cement. Corrugated asbestos cement. Fibrous plaster. 12-squares.

Colour Suggestion

WALLS ROOF TRIM DOORS EAVES

Natural timber. Grey-green Grey-green Lime yellow.


EASILY accommodated on a 50 ft. block, this threebedroom 12 sq. house has a good appearance, gained by linking carport to house entrance-way. This entranceway is partly roofed, partly open, so that an informal planting area can add interest to this feature.

A fireplace wall between living and dining rooms supplies both rooms with warmth. If the second fireplace wasn't wanted on the dining side, this opening could become a buffet or a floor-to-ceiling book shelf.

The architect has saved valuable space by substituting for the door between bedroom wing and laundry a passthrough for soiled clothes. Clothing can be dropped

through sliding panels into a basket in laundry.

Planned for timber construction, the house could be built in asbestos cement or brick. The roof is lowpitched and covered with corrugated asbestos cement.




the inside story...

The **inside** of your home is as important as the outside. Over 80 per cent of the area you see day in and day out consists of walls and ceilings. So it is important when you're building or buying a home that you remember the need for good walls

and ceilings.

Fortunately their cost usually represents only about 5 per cent of the total building investment. Thus there's no extravagance in selecting them for lifetime service, comfort and enjoyment. It is only logical that you should select for your walls and ceilings the interior lining material that will not only meet your requirements as to final appearance, but also bring you the advantages of fire-safety, acoustical control.



This beautiful home with its smooth, clean walls and ceilings illustrates perfectly the modern interior designs that can be achieved with Fibrous Plaster.

low-cost maintenance, long life and economy. These are the

Those who take the trouble to consider them always choose fibrous plaster (in one or more of its many forms) as the ideal interior lining material. Fibrous Plaster has been proven over the years — it is not some new idea still in the experimental stage — and it is still by far the most popular wall and ceiling material in Australia.

Fibrous Plaster is designed to last the lifetime of the building. Having its origin in rock, the plaster used in the manufacturing process is sturdy and highly resistant to knocks or scratches from furniture — impacts or children at play. Many Fibrous Plaster walls and ceilings installed in homes of comparatively early vintage still retain their original beauty today — despite rough usage and inadequate maintenance during their life.

The initial cost of Fibrous Plaster is low — probably lower than you think and certainly low when you consider its durability. Because of its qualities it helps in arranging finance and also it costs less than other materials to insure against fire. Should you ever wish to sell, Fibrous Plaster walls and ceilings promote a higher re-sale value.

Fire represents a major threat to the safety of your loved ones and to your life's investment — your home! Unlike some wallboards made of combustible fibres, Fibrous Plaster won't burn because it can't burn. It is one of your greatest shields


against fire spreading inside the house.

You should not overlook or underestimate the importance of quiet and privacy. When your walls are of Fibrous Plaster, you've taken a big step towards reducing noise transmission from one room to another. Because it exercises a high degree of sound absorption and acoustical control, it has been truly said that for peace and quiet you should use fibrous plaster.

Another of the great advantages Fibrous Plaster enjoys over

Another of the great advantages Fibrous Plaster enjoys over other materials is that it comes in so many different designs. In addition to flat sheets of any desired dimensions, Fibrous Plaster products include curved sheeting, acoustic tiles, cornices, lighting troughs, wall vents, baffle vents, fire-place surrounds, curtain pelmets, mural bas reliefs and many other ornamental features. It permits almost any concept of architectural design — from flat expanses of sheet to intricate ornamental work. Such treatment ensures that your home has that individualism and personalised appearance that is your very own.

Incidentally, all of these surfaces are unexcelled as a base for decoration. Whether paint, wall-paper or other coverings



FIBROUS PLASTER — The only interior lining material that can be moulded into any shape, is shown here in a graceful combination of straight lines and curves.

are used, the decorations endure because Fibrous Plaster provides a sturdy backing and lasting finish that both enhance their beauty and help prolong their life.

Of course it is always most advisable to obtain your Fibrous Plaster from a reputable manufacturer. The best way to ensure this is to check if he is a member of the Fibrous Plaster Association. Membership is granted only to manufacturers of proven integrity and skill. They not only manufacture and supply, but also provide the skilled tradesmen to carry out the fixing workmanship on site. When you deal with a member of the Fibrous Plaster Association all materials and workmanship comes from one responsible source ... completed to your satisfaction ready for painting.



For free advice or quotations you are invited to contact any member directly or if you prefer, write to or telephone the

FIBROUS PLASTER ASSOCIATION OF N.S.W.

24 BOND ST., SYDNEY. BU 4767, BU 6048

FOUNDATIONS

(Continued from page 15)

In Sydney it is common to use bush sand which already contains a proportion of lime and no lime is added when this is used.

Where local stone is available it may be preferred to use it for work up to floor level. Stones should be roughly squared, laid on their natural bed and bedded in cement mortar. On good ground for single-storey construction 18" stonework is sufficient. Under special conditions walls up to 24" wide may have to be used.

Most difficulties and failures are experienced on clay foundations, particularly when floaters—large loose stones—occur in the clay. Clay expands considerably when it is wet and shrinks in its dry stage. Everyone has seen the large cracks that open up in clay soils during dry weather. Drying and wetting of the ground in different seasons causes considerable movement of the foundations, the result of which is cracking in the structure above.

If one corner of a house rests on a floater and the remainder on clay this danger is increased. A difficulty sometimes encountered on rocky land is that what appears as solid rock may turn out to be a floater, resting on a layer of clay. In spite of all the extra hard work involved these floaters should be removed. If the floater cannot be removed altogether it is sometimes sufficient to "break its back", by blasting a few shots in it.

Generally the safest course with clay foundations is to dig down to a level so deep down that the ground is no longer affected by seasonal changes of moisture. But this is not always possible because in some cases this level may be as much as 15 feet down. Such difficulties are encountered particularly in the Adelaide area, to a lesser degree in Sydney's North Shore area and some of the Western Suburbs. Special types of footings have been designed for such situations where the normal strip footing is not applicable. They include inverted Tee shapes, deep beam and pier and beam footings. In the last-named piers are sunk down to a level of shale or bedrock and beams above ground level carry the weight of the walls above these piers. This, however, is an expert's job and where the ground appears difficult and treacherous the wisest course of action is to get an experienced engineer's or architect's advice.

Footings and foundation walls carry the weight of the walls and the roof. Most of the floor load is taken by piers which should be no further apart than 6 ft. from centre to centre. In Victoria red gum stumps are quite common for this purpose, while in N.S.W. 9" by 9" brick piers are mostly used.

An important item, however, that cannot be omitted is the damp-proof course. This course is built into the walls to prevent the moisture in the ground from travelling upwards through the walls. Lead is the ideal material for the purpose, but many other materials may be used. Aluminium is becoming quite common in N.S.W. and waterproof mortars of a proprietary make are often used in Victoria. If metal is used a strip of material is laid on each skin of the cavity wall below the level of the floor timbers and below and just above the level of a concrete slab. The cavity starts at least two courses below the damp-proof course. During bricklaying mortar drops down into the cavity. If this mortar remains lying above the damp course, moisture will penetrate through the mortar into the house. If it is allowed to drop down below the damp course no harm can be done. An added precaution is to leave weepholes—vertical joints without mortar—at the bottom of the external skin to allow any water to run out.

One other little point is worth remembering: Conscious of the dangers inherent in some foundation conditions local councils and many lending organisations require to be notified after the trenches have been dug. If the inspector has not arrived within 48 hours work on the foundations may proceed and trenches may be filled in.

no Shivery spots with

RAYBURN

(Reg. Trade Mark)

room heater's

because it goes DEEPLY through the largest rooms.

Rayburn gives more heat at less cost, burns for 10 hours with one fuelling. Rayburn warms every corner of the room — no draughts, no shivery spots.



TWO MODELS




RAYBURN

room heaters

White.

EAVES



This House Faces

Architect, John P. Ley, B.Arch., A.R.A.I.A., A.R.I.B.A. PLAN No. 25


Front or Side!

TYPICAL of the popular trend in asbestos cement construction, this neat house of 1190 square feet has three bedrooms, living room, separate dining room, kitchen, laundry and carport.

Lobby, dining room and courtyard are paved. A choice of paving could be made from cement, sawn stone, or terra-cotta paving tiles. The courtyard is roofed over (except for sun-trap which could be covered with a plastic material) and ties up carport with main house. The all-over design is unusual and distinctive.

ment of bedrooms-bathroom wing. The living, dining rooms and kitchen benefit in bigger living space.

The external sheeting is asbestos cement fixed vertically, with perhaps one or two walls in striated asbestos. Roof is a low-pitched gable covered with corrugated asbestos cement. Internally the laundry ceiling is raked with the roof pitch but the remaining ceilings are flat.



more hot water



(Available in white and cream enamel)

SLOW COMBUSTION COOKER

AND WATER HEATER

2 OVEN RAYBURN For big family cooking — big family cooking — big feature Rayburn with extra large hotplate for fast cooking and two big ovens. A large turkey-size roasting oven and a warming oven. Rayburn provides all the hot water a big family needs FREE! Controlled combustion makes Rayburn most economical, and beautiful new sheerline Rayburn adds streamlined beauty to your kitchen.







E142

(Capital City)
Slightly higher Tas.
and W.A.
CONVENIENT TERMS ARRANGED



New Dazzling white

SLOW COMBUSTION COOKER AND WATER HEATER FOR SMALL FAMILIES.

New, compact Clayton. Gives all the hot water a small family needs, cooks superbly too. hotplate, large oven, simple spin wheel control. Available in white and cream enamel.

PRICE WITH FLUE BOX AND BOILER

£64/10/0

Legs & cabinet opt, extra. (Capital City)

Slightly higher Tas. & W.A.

Made in Australia by ALLIED IRONFOUNDERS PTY. LTD. Distributed by Overseas Corporation (Aust.) Ltd.

BERREIS MAIL THIS COUPON TODAY INCHES To your nearest Overseas Corporation office.

588 Lt. Collins St., Melb. C.1. Vic.; 434 William St., Perth, W.A.; 383 Bulwarra Rd., Ultimo, N.S.W.; 293 Queen St., Brisbane, Qld.; 41 Magill Rd., Stepney, Adelaide, S.A.

me without obligation coloured literature on (tick which required).

RAYBURN


CLAYTON

NAME

9530

VARIETY IN 81 SQUARES

(Continued from page 7)



PLAN. 2.

A door leads from the living room to the carport and another leads from the laundry to an area which could be set aside for drying. Door from the kitchen to laundry is sliding-to avoid any danger of accident in the kitchen. There is no door between dining area and kitchen.

Scheme 2 features an adjustable louvre screen in the front of the house. It can be moved to let in the prevailing breeze, shut out the midday sun, and it gives a wonderful privacy to the living room. The French doors open out on to this sheltered area of the terrace.

ROOFING

(Continued from page 23)

One for grading (to drain off the rainwater), one for insulation (a function that the roof space fulfils in the pitched roof), and a surface to be walked on. Only if designed properly to solve all these problems will the flat roof give complete satisfaction. But then it will not be a cheap construction.

For covering the roof Marseilles patterned tiles are available in various red, tan and brown shades and also green and blue and may be glazed, semi or unglazed, the glossier tile being more waterproof. Tiles are wired to roof battens and their interlocking sides and heads ensure waterproofness when the pitch is no less than about 26°. Tiles may be used at a lower pitch down to 21° (and even as low as 15° has been used without trouble), but sarking must be used underneath, i.e., a layer of bitumenised felt which forms a barrier to whatever water may penetrate the tile joints. These joints, incidentally, ensure a certain amount of ventilation in the tiled roof which is important.

Concrete tiles are made to a similar size and pattern as clay tiles, but are somewhat heavier. There is a very large colour range in them.

Shingle tile or slates are rarely used here.


Sheet coverings include asbestos cement, corrugated steel sheets, aluminium, metal, and also copper and lead.

Steel sheets make a light roof which is important where transport is involved and they allow for light roof framing. Minimum pitch is about 1 in 12, but 1 in 16 or about 10° is a more recommendable minimum. The main point is that you must paint this roof regularly.

At least one firm is producing a metal tile. Multiple tiles (7 in one roof) are pressed out and stove enamelled. Aluminium may also be used as corrugated sheeting.

(Continued overleaf)

SHADEMASTER brings you aluminium awni



actually

Here's sun control at your fingertips. This new "Shademaster" awning rolls up or down in seconds and can be anchored in any position. "Shademaster" roll-up awnings give you protection



SHADEMASTER gives you

The introduction of double-coated HIGH GLOSS laths is the greatest advance made in venetian blind finishing. This mirror finish actually sheds dust and stays cleaner longer. The double-coated finish on "Shademaster" laths is tropic-proof and withstands extremes of climate. "Shademaster" venetian components also include plastic tape with the textured look; all metal head and rail and mechanism that assures a blind that works as well as it looks!



No Furnishing Fade Looks beautiful from inside, too!

Colour pattern is underneath as well as on top!



Washes Clean Just wash clean with a garden hose.

Waterproof - will keep out the rain.



FOR DESCRIPTIVE LITERATURE WRITE TO YOUR NEAREST DISTRIBUTOR:

N.S.W.:

Campbell Beaumont Pty. Ltd., 66 Myrtle Street, Chippendale,

N.S.W.

VICTORIA and

Venetian Supplies Pty. Ltd., 944 North Road, East Bentleigh, Vic.

SOUTH AUST .:

QUEENSLAND:

Premier Blinds Pty. Ltd., 84 Bowen Bridge Road, Bowen Bridge,

Brisbane, Queensland.


WEST AUST .:

Industrial Supplies & Consulting Service, Welshpool Road,

Welshpool, Perth, W.A.



PYROX-SCHWANK "WALL-RAY JNR." GAS RADIANT HEATER



Widespread warmth immediately you want

it, is a feature of the PYROX-SCHWANK Radiant Heater. It's the most efficient heater yet devised, and average cost is only 2d. per hour to run. Being wall-mounted it is ideal where space is at a premium, and most important, kiddies can't reach it. kitchens, bathrooms, dens, sunrooms, etc., it's a necessity!

PYROX GAS HOT WATER SERVICE

For unlimited hot water supply. Instantaneous hot water for a complete household is efficiently and economically supplied by the Pyrox Gas Hot Water Service, and you only pay for heating the water you use. storage tanks are required. The neat and compact Pyrox Unit is easily fitted to any wall.



Instantaneous Systems

FROM GAS COMPANIES AND HARDWARE STORES

Manufactured by:

PYROX LTD.

14-36 Queensberry St., CARLTON, VICTORIA. FJ 9121 69-71 Edward St., PYRMONT, NEW SOUTH WALES. MW 4417 PP-36

(Continued from page 58)

The aluminium tile is also a sheet with tile shapes pressed out and available in a number of attractive colours. The recommended minimum pitch is 21°.

Asbestos cement roofing which is made in two sizes of corrugations, standard and super six, can be used for a comparatively low pitch. Where extremely low pitches are required, seal the end laps with bitumen.

In addition to tiles and sheet materials membranes are available. They are usually bituminous felts, supplied in 1, 2 or 3-ply thickness and laid in bituminous compounds. This work is done by specialist firms which give several years guarantee, but upkeep is always a factor with bituminous felt roofs. Although used also on low-pitched roofs its main use is on flat timber roofs where it is laid on tongued and grooved boarding, and covered with gravel or similar material to protect the bitumen from the sun. Felt is also used as a waterproof membrane on concrete roofs and covered with sand, tiles, etc.

Construction Details. Leakages in roofs rarely occur in the main area but usually where a roof adjoins a vertical surface such as a parapet or a chimney. It is therefore extremely important to protect these danger points with metal flashings which divert water that might

otherwise penetrate the joint.

For habitable rooms in the roof, where windows in the gable walls are not possible, dormers are used. They have a certain picturesque charm but add waterproofing and construction problems to the cost.

Gutters whose function it is to collect rainwater and divert it to downpipes can be either in metal or asbestos cement and fixed to the fascia board (eaves gutter) or boxed in wood, lined with metal and situated anywhere in the roof. The latter presents more dangers since gutters have a tendency to be blocked by leaves, etc.

The roof is exposed to a great deal of cold and particularly heat and, therefore, insulation must be provided. Its simplest and frequently sufficient form is the well insulated roof space. The roof space may be ventilated through the tiles themselves, through open lining under the soffits, through openings in the gable walls, through specially manufactured ridge ventilators, according to the severity of conditions. This ventilation is also desirable for the protection of roof timbers. Insulation can further be provided in the form of mineral wool batts or blankets either directly over the ceiling, the joists, or under the roof skin. Other insulation materials are also available, among them metal-foil building paper which reflects the heat of the sun.

FOR A BLOCK WITH NO VIEW

(Continued from page 13)

The main bedroom has a large built-in wardrobe. A smaller wardrobe is situated just outside the second bedroom

All plumbing is grouped to save installation costs. The washing machine is placed in the bathroom. For laundry work a door leads from the bathroom to service yard.

By placing the house as close as possible to the southern boundary line, and providing a screen along the northern boundary, a private garden can be obtained.


The carport could have tool storage cupboards at one end.

For economy most of the large window area is fixed glass between studs placed at four feet centres. Bottom and top sections are hinged or sliding to provide ventilation. In the bedrooms the opening parts are placed at the side of the fixed glass.

The roof is flat but a skillion or simple gable roof could be substituted. On the north side the roof line continues straight over the terrace, but a portion of this roof has been left uncovered to give more light to the family room and to create an interesting effect.

For that touch of quality







R. B. DAVIES

the most beautiful lock ever made

Throughout the world, great buildings everywhere have been equipped with famous SCHLAGE locks-specified by foremost architects where only fittings of the most distinctive design, as well as functional usefulness, are acceptable.

Among the world's best designed homes—the great ocean liner "United States"—the Fabulous Fontainbleau Hotel at Miami-Cuba's fine 32-story apartment building at Havana, beautiful SCHLAGE Locks have been the logical choice.

Exclusive: Only SCHLAGE provides the choice of nine separate lock functions-for any door of any room.

PTY. LTD.

The Largest Manufacturers of Builders' Hardware in the Southern Hemisphere.


Write for free illustrated literature to: Dept. H. P.

R. B. DAVIES PTY, LTD.,

450 Illawarra Road, Marrickville, N.S.W.



Fontainbleau Hotel, MIAMI




The Perfect **Fireplace**


VOU need not have a fireplace that smokes. A chimney which draws properly is not a special dispensation of Providence, nor is it the result of some hit or miss method of construction. It is all a matter of design and the faithful following out of instructions by the tradesman.

The design of nearly every part of a building is now a matter of the correct and proved scientific principles involved, and a fireplace is no exception to the rule. It is known just what hot and cold air currents will do under certain circumstances. With this knowledge it is not difficult to construct a fireplace that will allow the hot, smoke-laden air to rise up the chimney, and prevent the colder, heavier air outside from forcing it back again.

The first diagram is a profile section through a correctly constructed fireplace. This shows the fundamentals that govern its efficient working.

(Continued next page)







STAINLESS STEEL WASH TROUGHS

Friction-frayed garments are Friction-frayed garments are
a thing of the past when
your laundry boasts a
gleaming new MORGAN'S
RADIANT Stainless Steel
Wash Trough because
RADIANT'S mirror smooth surface cannot harm even your most delicate fabrics.

Heavy gauge stainless steel. All-welded construction. New rounded corners. Single or double

compartments. Steel or wooden cabinets. optional. GUARANTEED FOR

For your home choose "RADIANT", from . LEADING HARDWARE STORES &

BUILDERS' & PLUMBERS' SUPPLIERS or mail this coupon to the manufacturers, L. J. MORGAN PTY. LTD., 192 Queensberry St., Carlton

Please send me a "Radiant" Trough leaflet by return.

SAFEGUARD YOUR HOME INSURANCE UNION FIRE (Founded 1797 in England)

53-57 Queen Street — Tel.: MA 2661 10 O'Connell Street — Tel.: BW 2711

BRANCHES AND AGENCIES THROUGHOUT THE COMMONWEALTH TRANSACT ALL CLASSES OF FIRE, ACCIDENT AND MARINE INSURANCE

The sloping back is necessary to throw the heat out into the room and to prevent most of it from going up the chimney. This back serves a twofold purpose and makes possible the smoke shelf above it, which prevents down draughts from sending the smoke back through the fire place into the room.

The width of the fireplace opening can be anything from 2 feet 3 inches to 3 feet 6 inches, but the height of the opening should not exceed 2 feet 3 inches. Two feet is

better.

The depth should never be less than 1 foot 6 inches. Should it be desired, for any reason, to make the height greater than that suggested, then the depth of the fireplace must be increased.

The brickwork (or stone) above the fireplace opening is supported on arch bars. The curved back should continue for at least 3 inches above the opening — preferably more. If this precaution is not taken, the back wall will defeat its own object and merely direct the smoke out into the room.

The throat is about 4 inches wide by the full width of the fireplace. Above this point the flue is "gathered" on until it assumes the proportions of 14 inches by 9 inches.

The hearth may contain a grate discharging into an ash pit if the floor is some distance above the ground, or to a small graded container, as shown in the diagram. A metal door on the outside makes the removal of the ashes an easy task.

This can only be done, of course, when the fireplace is on an outside wall. This is quite a common position for a fireplace, often used for the sole purpose of working in an ash pit.

But when a fireplace is on an outside wall a lot of the heat is lost. A fire soon warms up the bricks at the back

of the fireplace, and when this is within the house the room behind benefits considerably.

A fireplace on an outer wall can be pushed out so that no room space is taken up by it, but the recesses at the side of one within the house can be turned to considerable advantage, as shown in the second diagram.

The height of the chimney is another important factor, and this is one on which it is rather difficult to lay down rules. It is generally accepted that the top of the chimney should extend beyond the highest point of the roof, but this depends on the surroundings and the prevailing wind.

A much lower chimney will be efficient on the windy side of the house than that required on the lee. A roof causes the moving air to rise and drops it down on the other side. It will consequently draw the smoke up out of a low chimney on one side, but drive it back down a low chimney on the other side.

Furthermore, a high chimney on the windward side is always in danger of being overturned, especially if it is on an outside wall. A chimney in toward the centre of the structure is not only likely to draw better, but forms an admirable anchor for the roof.

Tall buildings, tall trees, or hills in close proximity to the house are apt to cause down draughts, and when these conditions occur, chimneys much higher than usual are called for. In hilly country one occasionally encounters a building site where some fold in the ground or perhaps the convergence of two or more valleys produce conditions where all the skill and experience in the world will not entirely obviate smoky fires under certain directions of wind. But such a circumstance is rare.

Like most things, building a smoke-free fireplace is very simple, if it is done right in the first place.





In the largest range of models and sizes for domestic, commercial and professional needs.

raemar

UNBLEMISHED HOT WATER is yours from time of installation through all the years you use your BRAEMAR. Hot water by BRAEMAR is singularly sediment and taint-free.

BRAEMAR construction is entirely non-corrosive copper all through, from cold-water intake to hot water outlet. No unpleasant corrosive taste. No sediment to trouble sensitive skin.

WHY YOU SHOULD HAVE BRAEMAR

BRAEMAR gives you the advantage of greater reliability and convenience — BRAEMAR is made by Australia's largest manufacturer of hot-water units — your guarantee of lifelong satisfaction and service.

BRAEMAR makes Hot Water

BRAEMAR makes Hot Water Units for every requirement of

every home, large or small. BRAEMAR will show you gladly the most economical way to put hot water on tap throughout your existing home; throughout the home you are planning. Write for full details of this FREE Planning Advisory Service.

Available at your nearest supplier.

Post Coupon FOR FREE LITERATURE

To: BRAEMAR ENGINEERING CO. (N.S.W.)
PTY, LTD.

Bonds Rd., Punchbowl, N.S.W. LF 0731
Please send me FREE illustrated literature
and information on BRAEMAR Hot Water Units.

(PRINT CLEARLY)	
	-
	(PRINT CLEARLY)

Required for
HOME
BEING
BUILT
Required for
EXISTING
HOME

State below it electric, town gas, L.P. gas, kero., distillate or solid fuel type.

HOME LIGHTING


(Continued from page 39)

Illumination of house numbers would frequently be of great help and external lighting is a deterrent for burglars. In addition many outdoor activities could be continued after dark such as garden work.

A particularly interesting application of light is the illumination of trees, flowers, pools and shrubs in the garden which take on an entirely new interest at night.

B. LIVING ROOM: Diffused overall light can be provided by means of indirect lighting reflected from the ceiling, by fluorescent tubes concealed in the pelmet boards or above fitments. The main requirement in the living room is flexibility. Have enough sources of light in correct positions to provide various effects to suit different activities. When listening to music or for quiet conversation the lights should be subdued, avoid overhead lights which shine in your eyes when leaning back in a lounge chair. When playing cards have the light directly over the table. For parties have good general illumination together with localised effects. Close work such as reading, writing, sewing is the most important lighting problem and the one most easy to solve. Together with localised light that illuminates the work you should always use subdued background lighting. The eyes become tired and strained if there is too much contrast between the well-lit work and the room in general. There are lamps available which provide just that general background illumination together with localised direct light.

C. DINING is often a further function of the living room. Lights should concentrate attention on the dining table. A ceiling fitting over the table can be used, or a standard lamp next to it or a recessed light in the ceiling will give you spotlight on the table together with subdued light for the rest of the room.



Detail of the kitchen section.

D. KITCHEN: The kitchen is a work room and the aim must be to provide a high level of general illumination together with localised lighting over working areas such as the sink, stove and work counter. In addition it is desirable to put light inside cupboards, ovens and refrigerator with plunger switches so that light is switched off and on automatically when doors are operated. This principle could well be extended to cupboards which are too deep to be seen clearly.

E. BEDROOMS: Bedrooms need good general illumination though the level need not be as high as in other rooms. Particular care must be taken that lights do not shine in your eyes when lying down. For the dressing table mirror it is essential to have light from two directions directed on the face or figure, either from both sides or from above and below, thus avoiding shadows. Two individual adjustable reading lamps should be provided for a double bedroom. When a bedroom is used as a study or sewing room the same conditions apply as in a living room.

F. BATHROOM: A small room with reflective surfaces the bathroom usually gets a sufficient quantity of light,

but not always the right kind. As mentioned for the dressing table, light at the shaving mirror should come from two directions.

G. UTILITY, LAUNDRY, GARAGE. Too often there is a tendency to be skimpy with these rooms. They are work rooms and need adequate light for the work to be performed even if it is not performed every day. Fluorescent is particularly suited for work bench. Fittings in halls and staircases should be planned to prevent accidents (avoid glare and contrasts) and so that light shines into hall cupboards, linen press, etc. Where this is not possible plunger switches should be fitted.

H. SPECIAL DECORATIVE EFFECTS. This is a possibility for home decoration which is often neglected and which leaves wide scope for imagination. Tubes concealed behind pelmet can highlight interesting curtain materials. Murals and pictures can be featured by spotlighting. Niches and recesses in walls or china display cabinets can be lighted inside.

Generally it pays to have an adequate number of light points installed. They do not cost very much when installed during construction and will not only safeguard your health and make your home pleasant but leave you prepared for any further development in lighting that the future may bring. When you employ fluorescent light remember that though dearer to instal it is much more economic to use except in positions where light is frequently turned on and

Your electricity bills will not be any higher by using a greater number of lights where you actually need them, because these lights will be turned off when not required for a specific visual task. You may feel you cannot afford a complete light installation desirable though it may be. The fact is you cannot afford to be without it.

A 3-STAGE PLAN

(Continued from page 11)

In the three stages of building . .


1. The bedroom wing can be omitted and the family room would then become the bedroom. The area would be 9.5 squares and the house would cost about £3,700 to build.

2. With two bedrooms, as shown in the plan, and with the family room, the area would be 13.2 squares and the cost approximately £5,100.

3. With three bedrooms and family room (extra bedroom is shown on plan with dotted lines) the house

would be 15.4 squares and cost £5,950.

The house is built of timber, with low-pitched gable roof sheeted with corrugated asbestos cement. The external walls of the living room and kitchen facing the street are stone and brick, respectively. The living room has highlight windows to the street for maximum privacy.



Counter and stools divide kitchen from dining area. Wall above is finished with vertical timber.

Eight reasons why today's homes are being fitted with

SPRING ROLLER INSECT SCREENS



A.R.C. Insect Screens Pty. Ltd. market the two best, most convenient, roller screens in the world. Phone or write for a representative to call, there's no obligation.



Sales Offices:

only cost.

a lifetime.

8. Screens are neat yet rugged—designed to last

579 Collins Street, 93 Prince's Highway, 27 Leichhardt Street Melbourne. Arncliffe, Sydney. MB 3151, MB 5279 LX 3251 Brisbane.

NAME

ADDRESS


Country Clients: Please send coupon for a measuring chart. ARCIS.13



WHITE ANT PROOFING


(Continued from page 34)

Brick and concrete piers.—Place caps on the damp-proof course of brick piers, then rest the bearers on them. If holding-down is needed, a ½-in. bolt may be cast into the concrete pier, the caps perforated, slipped over the bolts and bedded on cement mortar or tar and pitch mixed to a heavy consistency to seal caps and bolt-holes.



FIXING BEARERS AND TERMITE CAPS TO WOODEN STUMPS

Wooden stumps.—If caps are nailed on, all nail heads must be soldered over. Where holding-down is required, do not spike nail bearers, as this perforates the caps. Instead, use a bent bolt coach-screwed to the stump.



ANOTHER METHOD OF FIXING TERMITE CAPS

Fireplaces, porches, terraces.—Shields should be inserted above damp-proof course in brickwork, or bonded into concrete. Joins with shields from adjoining walls should be soldered with a 1 in. lap. In wooden buildings, where fireplaces, etc., are isolated, shields must be fitted all round.

External walls.—Shield is laid on damp-proof course and projects and turns down on inside face only.


Mortar.—All mortar below shield level should consist of 1 part cement, 1 part lime and 6 parts sand, as termites can penetrate poor quality mortar and gain access to structural timber via the cavity.

Weep Holes.—The cavity should be concrete-filled up to damp-proof course and shield level, and weep holes positioned in the first course of bricks above the shield. Weep holes below the shield allow termites to enter the cavity and use it as access to timber.

Internal Walls—A shield 5 inches wider than the wall is laid on the damp-proof course and projected at least ½ in. horizontally with a turn down of 2 ins. at 45° on both sides of wall. Where walls meet, T-junction shields with mitred joints should be used.

Concrete Floors.—A continuous concrete course at least 3 ins. thick, projecting 3 ins. both inside and outside the walls, should be laid on the foundation walls. Slope the course on the outside to allow for rainwater run-off. Concrete floors should be butted to this course, the junction and all expansion joints poisoned with creosote oil at the rate of 1 gallon to 100 feet of joint. All structural timber (Continued on page 70)

66 PLANS FOR YOUR DREAM HOME



Dream homes need dream windows . . . "Slimline" Casements K-M Steel

Make your dream home really true, with the grandest windows you can buy - and they cost no more than ordinary windows. For the spacious view, for the best light, for garden-fresh air to order, specify K-M Steel "Slimline" Casement Windows . . . the dream windows that every woman wants ... every builder prefers ... every architect recommends.

- In single frame or window-wall, K-M Steel Casements add grace and distinction.
- They will not shrink nor swell in any weather; they are rattle-free for life.
- Built so that K-M clip-on insect screens can readily be fitted on the inside.
- They open and close smoothly with gear operation, without removing the screens.
- Easy and economical to install in any type of construction.

Your choice of design can be met from the limitless combinations of the sixty K-M stock sizes. It will pay you well to select K-M.

K-M STEEL PRODUCTS LTD.

(A member of the "Cyclone" group of Companies)

VIC.: Harcourt Pde., Richmond, JB 1361. N.S.W.: Cnr. Milperra Rd. and Edgar St., Revesby, UU 8594

S. AUST.: Parbury, Henty & Co. (S.A.) Ltd., 416 King William St., Adelaide, W 6621.

QLD.: C clone Company of Aust. Ltd., Robinson Rd., Geebung, LX 1051.

W. AUST.: Cyclone Company of Aust. Ltd., Brown & Lime Sts., East Perth, BF 3171.

TAS.: Cyclone Company of Aust. Ltd., Fawkner Avenue, King's Meadows, Launceston, J 2481

POST COUPON NOW FOR DETAILS

Please send me booklet of K-M Steel Windows.

SCHEMES

Super

SCHEME 2

LOUNGE-DINING ROOM Celling: Chartreuse Super Matt. Walls: Dawn Grey, Super Matt. Feature Wall: Deep Jade, Super Matt.

Door: As Walls, Super Satin.

HALL & PASSAGE
Ceiling: Deep Jade, Super Matt.
Walls: Chartreuse, Super Matt.
Door: Dawn Grey, Super Satin.
BEDROOM (1)
Ceiling: 1 Deep Jade, Wedgewood Blue, Super Matt.
Walls: Off White, Super Matt.
Door: As Ceiling Super Satin.
BEDROOM (2)
Ceiling: Candy Pink, Super
Matt.

Ceiling: Candy Pink, Super Matt.
Walls: Lilac, Super Matt.
Door: As Ceiling, Super Satin.
KITCHEN
Ceiling: Chartreuse, Super Matt.
Walls: Dawn Grey, Super Satin.

Hi Gloss. Architraves, Fascia, etc.: White, Hi Gloss. Door and Eaves (Timber): Tur-quoise, Hi Gloss. Roof: Grey, Roof Guard.

Door: We Enamel.

EXTERIOR

SCHEME 5

Ceiling: China Blue, Super Matt.
Walls: Mushroom, Super Matt.
Door: As Wall, Super Satin.
HALL & PASSAGE
Ceiling: Deep Jade, Super Matt.
Door: As Celling, Super Matt.
Door: As Celling, Super Matt.
Door: As Celling, Super Satin.
BEDROOM (1)
Ceiling: Glacier Green, Super Matt.
Walls: Lavender, Super Latex.

Matt.
Walls: Lavender, Super Latex.
Robes: Candy Pink, Super Satin.
Door: As Wall, Super Satin.
BEDROOM (2)
Celling: Frosty Blue, Super Matt.
Walls: Cloud Note Candon Can

Walls: Cloud Pink, Super Latex. Robes: Wedgewood Blue, Super

Upper Cupboards, Cupboard
Frames and Kitchen Door:
White, Super Enamel.
Lower Cupboards: Burnt Clay,
Super Enamel.

BATHROOM AND SHOWER Ceiling: White, Super Satin.
Walls: China Blue, Super Super

Arichitraves, Skirting and Windows: White, Super Satin.
Utility Areas: use White, Super Enamel

Walls and Downpipes: Coral,

Wedgewood Blue, Super

Door: As Wall, Super Satin.
KITCHEN
Ceiling: Primrose, Super Satin.
Walls: China Blue, Super Satin.
Upper Cupboards: Wedgewood
Blue, Super Enamel.
Lower Cupboards: Maypole
Pink, Super Enamel.
Cupboard Frames: White Super
Enamel.
Door: As Walls, Super Enamel.

BATHROOM AND SHOWER Ceiling: Candy Pink, Super Satin. Glacier Green, Super

Enamel.

Door: Carnation Red, Super
Enamel.

EXTERIOR

Walls: Gull Grey, Hi Gloss. Trim: White, Hi Gloss. Eaves: Flamingo, Hi Gloss. Door: Lagoon Blue, Hi Gloss.

SCHEME 6

LOUNGE—DINING ROOM Ceiling: Dawn Grey, Super Matt.

Matt.
Walls: Deep Jade, Super Matt.
Dining Wall: Burnt Clay, Super Matt.
Door: As Walls, Super Satin.
HALL & PASSAGE
Ceiling: Dawn Grey, Super

HALL & PASSAGE
Ceiling: Dawn Grey, Super
Matt.
Walls: Deep Jade, Super Matt.
Door: As Walls, Super Satin.
BEDROOM (1)
Ceiling: Candy Pink, Super
Matt.
Walls: Lavender, Super Latex.
Robes: Cloud Pink, Super Satin.
Door: As Wall, Super Satin.
DEDROOM (2)
Ceiling: Off White, Super Matt.
Walls: Olive, Super Latex.
Robes: Mushroom, Super Satin.
Door: As Wall, Super Satin.
BEDROOM (3)
Ceiling: Primrose, Super Matt.

Walls: Mist Blue, Super Latex. Door: China Blue, Super Satin. KITCHEN

Ceiling: Fiesta Yellow, Super Satin.

Satin.
Walls: Dawn Grey, Super Satin.
Upper Cupboards, Cupboard
Frames and Kitchen Door:
White, Super Enamel.
Lower Cupboards: Delft Blue,
Super Fnamel.

BATHROOM AND SHOWER
Ceiling: Nile Green, Super
Satin.
Walls: Cloud Pink, Super

Enamel.

Door: White, Super Enamel.

EXTERIOR

Walls: Paradise Blue, Hi Gloss.
Trim: White, Hi Gloss.
Eaves: Coral Hi Gloss.
Door: Turquoise Hi Gloss.
Architraves, Skirting and Windows: White Super Satin.
Utility Areas: White Super Enamel.

SCHEME A

LOUNGE—DINING ROOM Ceiling: Primrose, Super Matt. Walls: Lilac, Super Matt. Fireplace Wall: Sea Green, Super Latex. Door: As Wall Super Satin.

Door: As Wall Super Satin.
BEDROOM (1)
Ceiling: Lilac, Super Matt.
Walls: Aqua, Super Latex.
Bedhead Wall: Cloud Pink,

Bedhead Wall: Cloud Pink, Super Latex. Door: Lilac, Super Satin. BEDROOM (2) Ceiling: Glacier Green, Super Matt. Walls: Lavender, Super Latex. Bedhead Wall: Suntan, Super Latex.

Latex.

Door: Dawn Grey, Super Satin.

Architraves, Skirting and Windows: White Super Satin.

Utility Areas: White, Super Enamel.

KITCHEN & FAMILY ROOM

Ceiling: Candy Pink, Super

Enamel.

oor: Wedgewood Blue, Super Enamel.

Walls: Sun Yellow, Hi Trim: White, Hi Gloss. Eaves: Salad Green. Door: Horizon Grey, Hi Gloss.

SCHEME 11 Walls: Lilac, Super Satin. Upper Cupboards: Chartreuse, Super Enamel. Lower Cupboards: Carnation Red, Super Enamel. Frames: White, Super Enamel. Kitchen Door: As Walls, Super

LOUNGE—DINING ROOM
Ceiling: Chartreuse, Super Matt.
Walls: Lilac, Super Matt.
Door: Lilac, Super Matt.
Door: Lilac, Super Matt.
Door: Lilac, Super Matt.
BEDROOM (1)
Ceiling: Lilac, Super Latex.
Bedhead Wall: Sea Green,
Super Latex.
Door: Lilac, Super Satin.
BEDROOM (2)
Ceiling: Daffodil, Super Matt.
Walls: Dawn Grey, Super Matt
or Super Latex.
Door: As Wall Super Satin.
KITCHEN
Ceiling: Chartreuse, Super Satin. LOUNGE-DINING ROOM

Ceiling: Chartreuse, Super Satin.

LOUNGE-DINING ROOM HALL & PASSAGE

Ceiling: Frosty Blue, Super Matt. Walls: Sea Green, Super Latex Short Wall: Suntan, Super Latex. Super

Door: Frosty Blue, Super Satin.

BEDROOM (1)

Ceiling: Candy Pink, Super Matt. Walls: Cloud Pink, Super Matt Malt: Cloud Pink, Super Matt or Super Latex. Robes: China Blue, Super Satin. Door: As Wall, Super Satin.

BEDROOM (2)

Ceiling: Wedgewood Blue, Super Matt. Walls: Daffodil, Super Latex. Robes: Dawn Grey, Super Satin. Door: Dawn Grey, Super Satin. Architeraves, Skirting and

BATHROOM AND SHOWER Ceiling: Off White, Super Satin. Walls: Olive, Super Enamel. Door: Daffodil, Super Enamel. EXTERIOR Walls: Bungalow Cream, Hi Gloss. Trim: White, Hi Gloss. Eaves: Ripple Green, Hi Doors: White, Hi Gloss.

SCHEME 12

Windows: White, Super Satin.
Utility Areas: White, Super
Enamel.

KITCHEN

Ceiling: Chartreuse, Super Satin.
Walls: Dawn Grey, Super Satin.
Upper Cupboards: Salad Green,
Super Enamel.
Lower Cupboards, Cupboard
Frames and Kitchen Door:
White, Super Enamel.

BATHROOM AND SHOWER Ceiling: Nile Green, Super

Satin.

Satin.

Walls: Mushroom, Super Satin.

Door: Dawn Grey, Super

Enamel.

EXTERIOR

Walls: Shadow Blue, Hi Gloss. Trim: White, Hi Gloss. Eaves: Sun Yellow, Hi Gloss. Door: Flamingo, Hi Gloss.

SCHEME

LOUNGE-DINING ROOM Ceiling: Glacier Green, Super

Walls: Mushroom, Super Matt. Door: As Wall, Super Satin.

BEDROOM (1)

Ceiling: Candy Pink, Super Matt. Walls: Lilac, Super Matt. Bedhead Wall: Nile Green, Super Matt. Door: As Wall, Super Satin.

BEDROOM (2)

Ceiling: Primrose, Super Matt. Walls: Dawn Grey, Super Matt or Super Latex. Door: As Wall, Super Satin.

BEDROOM (3)

LOUNGE

Ceiling: Cloud Pink, Super Matt. Matt. Walls: Sea Green, Super Latex. Door: Candy Pink, Super Satin.

BEDROOM (1)
Ceiling: Glacier Green, Super Matt.
Walls: Lilac, Super Matt.
Door and Robes: As Wall, Super Satin.

Architraves, Skirting and Windows: White, Super Satin.
Utility Areas: White, Super Enamel.

KITCHEN

Ceiling: Deep Jade, Super Satin.
Walls: Chartreuse, Super Satin.
Upper Cupboards, Frames:
White, Super Enamel.
Lower Cupboards: Burnt Clay,
Super Enamel.
Door: As Wall, Super Enamel.

BATHROOM AND SHOWER

Celling: Olive, Super Satin. Walls: Off White, Super Enamel. Door: Candy Pink, Super Enamel.

EXTERIOR

Walls: Flame, Super Matt. Trim: White, Hi Gloss. Eaves: Paradise Blue, Hi Gloss. Door: White, Hi Gloss.

SCHEME 16

HALL & PASSAGE Ceiling: Cloud Pink, Super Matt. Walls: Dawn Grey, Super Matt or Super Latex. Island Wall: Chartreuse, Super Matt or Super Latex. Door: As Wall, Super Satin.

Ceiling: Cloud Pink, Super Matt. Walls: Dawn Grey, Super Matt or Super Latex. Door: As Walls, Super Satin.

KITCHEN

Ceiling: White, Super Satin.
Walls: Dawn Grey, Super Satin.
Upper Cupboards: Deep Jade,
Super Enamel.
Lower Cupboards: Maypole Pink,
Super Enamel.
Frames and Kitchen
White, Super Enamel.

BATHROOM AND SHOWER

Ceiling: Deep Jade, Super Satin.
Walls: Glacier Green, Super
Enamel.
Door: White, Super Enamel.

EXTERIOR

Walls: Claret, Hi Gloss. Trim: White, Hi Gloss. Eaves: Sun Yellow, Hi Gloss. Door: Paradise Blue, Hi Gloss.

Ceiling: Primrose, Super Matt.
Walls: Mushroom, Super Satin.
Upper Cupboard Frames: White,
Super Enamel.
Lower Cupboards: Salad Green,
Super Enamel.
Door: As Wall, Super Enamel.

BATHROOM AND SHOWER

Satin.

BEDROOM (2)
Ceiling: Candy Pink, Super Matt.
Walls: Glacier Green, Super Matt or Super Latex.
Door and Robes: As Wall, Super Satin. Walls: Frosty Blue, Super

EXTERIOR

BEDROOM (3)
Ceiling: Primrose, Super Matt.
Walls: Mist Blue, Super Latex.
End Wall: Breton Blue, Super End Wall: Breton Blue, Super Latex. Door: Dawn Grey, Super Satin. Super

SCHEME 17

LOUNGE—DINING ROOM Ceiling: Glacier Green, Super Matt.

Walls: Mushroom, Super Matt. North Wall: Deep Jade, Super

Matt. Door: As Wall, Super Satin.

HALL & PASSAGE
Ceiling: Deep Jade, Super Matt.
Walls: Glacier Green, Super
Matt. As Wall, Super Satin.

BEDROOM (1)
Ceiling: Chartreuse, Super Matt.
Walls: Dawn Grey, Super Matt
or Super Latex.
Door: As Wall, Super Satin.
Robes: White, Super Satin.

BEDROOM (2)
Ceiling: Frosty Blue, Super
Matt.

Walls: Cloud Pink, Super Matt or Super Latex. Door: As Wall, Super Satin. Robes: Wedgewood Blue, Super Cloud Pink, Super Matt

Architraves, Skirting and Win-

dows: White, Super Satin.
Utility Areas: White, Super
Enamel.

BEDROOM (3)
Ceiling: Lilac, Super Matt.
Walls: China Blue, Super Matt.
End Wall: Candy Pink, Super
Satin.

Door: As Wall, Super Satin.

KITCHEN

Ceiling: Chartreuse, Super Satin.
Walls: Lilac, Super Satin.
Upper Cupboards, Frames, Kitchen Door: White Super
Enamel.

ower Cupboards: Deep Jade, Super Enamel.

BATHROOM AND SHOWER Ceiling: Primrose, Super Satin.
Walls: Nile Green, Super
Enamel.

Door: White, Super Enamel. EXTERIOR

Walls: Paradise Blue, Hi Gloss. Trim: White, Hi Gloss. Eaves: Claret, Hi Gloss. Door: Coral, Hi Gloss.

SCHEME 18

LOUNGE Ceiling: Olive, Super Matt. Walls: Mushroom, Super Matt. Door: As Wall, Super Satin.

BEDROOM (I)
Ceiling: Lilac, Super Matt.
Walls: Deep Jade, Super Matt.
Door: As Wall, Super Satin.

BEDROOM (2) Ceiling: Mushroom, Super Matt. Walls: China Blue, Super Matt. Door: As Wall, Super Satin.

KITCHEN—DINING ROOM Ceiling: Olive, Super Matt. Walls: Lilac, Super Satin. Upper Cupboards and Kitchen

Door: As Wall, Super Enamel. Lower Cupboards: Flame, Super Enamel. Frames: White, Super Enamel.

BATHROOM AND SHOWER BATHROOM AND SHOWER
Ceiling: Deep Jade, Super Satin.
Walls: Primrose, Super Satin.
Bath: Persian Brown.
Door: As Wall, Super Enamel.
Architraves, Skirting and Windows: White, Super Satin.
Utility Areas: White Super Enamel.

EXTERIOR Walls: Dove Grey, Hi Gloss.
Trim: White, Hi Gloss.
Eaves: Buttercup, Hi Gloss.
Door: Flamingo, Hi Gloss.

SCHEME 19

LOUNGE—DINING ROOM Ceiling: Lavender, Super Latex. Walls: Olive, Super Latex. Door: As Wall, Super Satin.

BEDROOM (I)
Ceiling: White, Super Latex.
Walls: Breton Blue, Super
Latex.
Door: Wedgewood Blue, Super
Satin

Latex.

Door: Wedgewood Blue, Super Satin.

Robes: Chartreuse, Super Satin.

Trim: White, Super Satin.

BEDROOM (2) Ceiling: Aqua, Super Latex. Walls: Lavender, Super Latex. Door: Lilac, Super Satin.

BATHROOM AND SHOWER Ceiling: Flame, Super Satin. Walls: Dawn Grey, Super Satin. Door: White, Super Enamel. Bath: Grey. KITCHEN AND LAUNDRY Ceiling: Chartreuse, Super

Satin.
Walls: Dawn Grey, Super Satin.
Upper Cupboards, Frames, and
Kitchen Door: White, Super
Enamel.
Lower Cupboards: Burnt Clay,
Super Enamel.
Architraves, Skirting and Windows: White, Super Satin.
Utility Areas: White, Super
Enamel.

EXTERIOR
Walls: White, Hi Gloss.
Trim: Black, Hi Gloss.
Eaves: Maypole Pink, Super Eaves: Maypore Matt. Moor: Wedgewood Blue, Super

SCHEME 21

LOUNGE-DINING ROOM

—HALL AND PASSAGE
Ceilings: Chartreuse, Super Matt.
Walls: Dawn Grey, Super Matt or Super Latex.
Fireplace Wall: Burnt Clay:
Super Matt.
Stairwell Wall: Salad Green,
Super Matt or Super Latex.
Doors: As Walls, Super Satin.

BEDROOM (I)

BEDROOM (I)

Ceiling: China Blue, Super Matt.

Walls: Mushroom, Super Matt.

Bedhead Wall: Cloud Pink,

Super Matt.

Robes and Door: As Wall, Super

Satin.

Trim: White, Super Satin.

BEDROOM (2)

BEDROOM (2)

Ceiling: Cloud Pink, Super Matt.

Walls: Frosty Blue, Super Matt.

Bednead Wall: Candy Pink,

Super Matt.

Door and Robes: As Wall,

Super Satin.

Trim: White, Super Satin.

BEDROOM (3)
Ceiling: Candy Pink, Super
Matt.
Walls: Glacier Green, Super
Matt. Bedhead Wall Super Matt. Jade. Deep Wall:

KITCHEN

Ceiling: White, Super Satin.
Walls: Lilac, Super Satin.
Door: Salad Green, Super
Enamel.

Enamel.
Upper Cupboards: Chartreuse
Super Enamel.
Lower Cupboards: Burnt Clay,
Super Enamel.
Cupboard Frames: White, Super
Enamel.

BATHROOM AND SHOWER

Ceiling: Wedgewood Blue, Super Satin.
Walls: Primrose, Super Satin. Bath Wall: China Blue, Super Enamel.
Door: Flame, Super Enamel.
Architraves, Skirting and Windows: White, Super Satin.
Utility Areas: White, Super Enamel.

EXTERIOR Lower Walls: Breton Blue, Super Latex. Upper Walls: Mist Blue, Super Latex. Infill Panels: Candy Pink, Super Matt.
Eaves: Chartreuse, Super Matt.
Doors: Chartreuse, Super Super Enamel. Trim: White Super Enamel.

SCHEME 22

LOUNGE-DINING ROOM HALL AND PASSAGE

Ceiling: Dawn Grey, Super Matt or Super Latex.
Walls: Chartreuse, Super Matt or Super Latex.
Dining Wall: Salad Green, Super Matt or Super Latex.
Doors: As Walls, Super Satin.

BEDROOM (I)
Ceiling: Candy Pink, Super
Matt.
Walls: Aqua, Super Matt.
Door: As Walls, Super Satin.

BEDROOM (2) Ceiling: Glacier Green, Super Matt. Matt.
Walls: Orchid, Super Latex.
Robe Wall: Nile Green, Super
Satin.
Door: Candy Pink, Super Satin.

KITCHEN

KITCHEN
Ceiling: Dawn Grey, Super Matt.
Walls: Chartreuse Super Satin.
Upper Cupboard and Frames:
White Super Enamel.
Lower Cupboards: Burnt Clay,
Super Enamel.
Door: As Wall, Super Enamel.
Architraves, Skirting and Windows: White, Super Satin.
Utility Areas: White, Super
Enamel.

BATHROOM AND SHOWER Ceiling: Daffodil, Super Satin. Walls: Off White, Super Enamel. Door: Wedgewood Blue Super Enamel

EXTERIOR

Walls: Shadow Blue, Hi Gloss.
Trim: White, Hi Gloss.
Eaves: Flame, Super Matt.
Door: Royal Blue, Super Enamel.

SCHEME 23

Colling: Olive, Super Matt.
Walls: Primrose, Super Matt.
Or Super Latex.
Dining Wall: Suntan, Super Latex.
Door: Olive, Super Satin.
HALL & PASSAGE
Ceiling Olive, Super Matt.
Walls: Off White, Super Matt
or Super Latex.
Door: Olive, Super Matt.
Walls: Off White, Super Matt
or Super Latex.
Door: Olive, Super Satin.
BEDROOM (1)
Ceiling: Lilac, Super Matt.
Walls: Aqua, Super Latex.
Robe Wall: White, Super Satin.
Door: White, Super Satin.
BEDROOM (2)
Ceiling: Deep Jade, Super Matt.
Walls: Daffodil, Super Matt.
Walls: Daffodil, Super Matt.
Walls: Daffodil, Super Matt.
To Super Latex.
Robe Wall: Lilac, Super Satin.
Door: Lilac, Super Satin.
Door: Lilac, Super Satin. ROOM LOUNGE-DINING

Windows: White, Super Satin. Utility Areas: White, Super Enamel. KITCHEN

Ceiling: Flame, Super Satin. Walls: Dawn Grey, Super

Walls: Dawn Grey, Super Satin. Upper Cupboards, Frames and Kitchen Door: White, Super Enamel. Lower Cupboards: Delft Blue, Super Enamel.

Super Enamel.

BATHROOM AND SHOWER
Ceiling: Cloud Pink, Super Ceiling: Cloud Satin.
Satin.
Walls: Chartreuse, Super

Enamel. coor: White, Super Enamel. EXTERIOR

Walls: Bungalow Cream, Hi Gloss.
Trim: White, Hi Gloss.
Eaves: White, Super Matt.
Door: Highland Green, Hi Gloss.

SCHEME 24

LOUNGE—DINING ROOM
Ceiling: Frosty Blue, Super
Matt.
Walls: Olive, Super Matt or
Super Latex.
End Dining Wall: Burnt Clay,
Super Matt.
Door: As Wall, Super Satin.
HALL & PASSAGE
Ceiling: Frosty Blue, Super
Matt.
Short Wall: Off White, Super
Matt or Super Latex.
Door: As Wall, Super Satin.
BEDROOM (1)
Ceiling: Nile Green, Super
Matt.
Walls: Primrose, Super Matt or
Super Latex. LOUNGE-DINING ROOM

Waits: Frimrose, Super Matt of Super Latex. Bedhead Wall: Flame, Super Matt or Super Latex. Door and Robes: As Wall Super Satin.

Satin.
BEDROOM (2)
Ceiling: Primrose, Super Matt.
Walls: China Blue, Super Matt.
Robe: Wedgewood Blue, Super Robe: Wedgewood Blue, Sup-Satin. Door: As Wall, Super Satin.

BEDROOM (3)
Ceiling: Daffodil, Super Latex
Walls: Dawn Grey, Super Matt
or Super Latex.
Robe: Maypole Pink, Super
Satin.
Door: As Wall, Super Satin.

KITCHEN
Ceiling: Burnt Clay, Super
Satin.
Walls: Chartreuse, Super Satin.
Door: White, Super Enamel.
Upper Cupboards: Burnt Clay,
Super Enamel.
Lower Cupboards White, Super
Enamel.
Frames: White, Super Enamel.

BATHROOM AND SHOWER Ceiling: Candy Pink, Super Satin. Walls: Lilac, Super Satin.

Door: China Blue, Super
Enamel.

EXTERIOR Walls: Lagoon Blue, Hi Glos Trim: White, Hi Gloss. Eaves: Coral, Hi Gloss. Door: Sun Yellow, Hi Gloss. Hi Gloss.

Beautiful colour schemes for the rest of the plans in this book have been worked out by expert colour consultants at the DULUX Colour Centres. If you would like a free colour scheme, simply write, phone or call, on your nearest DULUX Colour Centre, who will be happy to supply one.

DULUX COLOUR CENTRES

SYDNEY: 1st Floor, Dymocks Building, 426 George
Street. BL 1144/5.

MELBOURNE: 3rd Floor Century Buildings,
125 Swanston Street. C 4466/7/8.

ADELAIDE: 1st Floor, Elizabeth House, North
Terrace. W 4871/2.

BRISBANE: 1st Floor, Piccadilly Arcade, Queen and
Adelaide Streets.

TASMANIA: 63 Flizabeth Streets Laurceston

TASMANIA: 63 Elizabeth Street, Launceston.

PERTH: 1st Floor, National Mutual Life Assurance Building, 81 St. George's

Terrace. NEW ZEALAND: Wellington- 56 Willis Street.



Solid core Doors and Panels by Rosco are strong and firm to the touch . . . you can feel the extra weight and quality in the solid core, and the smooth, even surface of the handpicked veneer.

It pays . . . if you want a lasting job, with a truely fine appearance . . . to specify Rosco Solid Core throughout. Distributed by:


PTY. LTD.

695 Gardener's Road, Mascot, N.S.W. - MU 3696




(Continued from page 66)

should rest ON the floor - none should pass through it. Termite access points.—Fireplaces, porches, steps, terraces and projecting weatherboards often provide white ants with




TERMITE-PROOF CONCRETE GROUND FLOORS

routes to food timber. All must be fitted with shields or isolated by a gap of approximately 2 ins. from the rest of the building. Wooden steps may be placed on capped piers or stumps. Weatherboards should not be carried down closer than 2 inches above soil level, and care should be taken to clear away debris which might come to rest against them and provide termites with access routes. Provision should be made to inspect stumps and piers under houses at least once a year, more often in badly infested areas such as Queensland.



SHIELDING A BRICK VENEER BUILDING

Termite-resistant timbers.—A number of the denser eucalypts: ironbarks, river and forest red gums, most boxes, wandoo, jarrah, ironwood, tallow-wood, bloodwood and turpentine, are considerably resistant to termite attack.



SHIELDING A BRICK BUILDING

These timbers should be used for stumps and for other unprotected woodwork in contact with the ground. In northern areas, where the termite species "mastotermes" is prevalent, cypress pine should be used. This timber has outstanding resistance to this termite. Most light-coloured and lightweight hardwood timber, and most softwoods, have little resistance to termites.

Creosote brushing and dipping.—Superficial coatings of

this oil do not give permanent protection.

Drainage pipes and conduits.—These are often used by termites as access routes. Where they are situated under the floor, and in contact with the ground, they should be fitted with special metal shields. Pipes driven in to the ground for earthing radios, etc., should be positioned at least 3 inches from the wall.



In conjunction with their associate Company

LEHMANN BROS. PTY. LTD

invite you to visit their showrooms at 17A Bridge Street, Sydney — 660 Botany, Road, Alexandria.



Tiles from all over the world . . . England, Germany, France, Spain, Portugal, Hong Kong, Japan and Australia, all displayed to give you Sydney's finest selection of Wall and Floor Tiles. Lehmann Bros. Pty. Ltd., are recognised throughout the trade as Leaders in their craft. Their tile laying experts will be pleased to quote for any tile fixing.

Sanitaryware Specialists Since 1777



Showrooms: CITY, 17A BRIDGE ST. BU 2252-3-4 ALEXANDRIA, 660 BOTANY ROAD. MU 2213 We cordially invite you to call into either of our showrooms . . . there, we know you will be really interested to just walk around and inspect what is without doubt, Australia's largest and best range of imported and locally made tiles, taps, basins, sanitaryware and other p.c. items.

TYLORS (AUSTRALIA) PTY. LTD., 17A BRIDGE STREET, SYDNEY.

Please forward me coloured booklet showing your large, modern range of Sanitaryware and P.C. items.

NAME

ADDRESS ...

DH




It's Amazing...

the swing to



available
in
SIX
attractive
colours
for



BATHROOM, KITCHEN AND LAUNDRY WALLS

Bathroom, kitchen and laundry walls take on a new beauty when lined with Wunderlich "Duradec", the modern plastic surfaced asbestoscement decorated sheet. And the walls will stay bright and new. Priced to fit most budgets, homebuilders now prefer "Duradec" for it meets all modern requirements of decorated wall boards.

The coloured surface, blue, grey, pink, black, green or buff,—bonded into the sheet—is laboratory tested. Wash it, scrub it. It is wear and scratch-proof, fire resisting, strongly resistant to soaps, mild alkalis and acids, steam, heat and stains. The colours do not fade, do not require waxing or other preservative treatment. Four waste-saving sheet sizes are available in New South Wales and Queensland:

7' x 3', 7' x 4', 6' x 3', and 6' x 4'.

Note: In Victoria and South Australia 6' x 3' and 6' x 4' sheets only— Buff not available.

FREE Write to Wunderlich Limited, Dept. DD, at Sydney, Melbourne, Brisbane or Adelaide for illustrated folder and prices. "WUNDERBRITE"
ALUMINIUM
MOULDINGS

П

I

Capping No. 1900

Joint Strip No. 1901





Ext. Angle No. 1902

Int. Angle No. 1903

Wunderlich



READILY AVAILABLE FROM AUTHORISED HARDWARE AND TIMBER MERCHANTS

10.8DD.12

Digitized by:



ASSOCIATION
FOR
PRESERVATION
TECHNOLOGY,
INTERNATIONAL
www.apti.org
Australasia Chapter

BUILDING TECHNOLOGY HERITAGE LIBRARY

https://archive.org/details/buildingtechnologyheritagelibrary

from the collection of:

Miles Lewis, Melbourne

funding provided by:

the Vera Moore Foundation, Australia

